



# HOBO UX90 State Logger - UX90-002M

### Overview

The HOBO Light On/Off data logger monitors indoor light changes with an internal sensor and records light on and off conditions, making it ideal for building energy audits and light usage analysis.

The HOBO UX90-002 Light On/Off Data Logger is available in a standard 128 KB memory model (UX90-002) capable of 84,650 measurements and an expanded 512KB memory version (UX90-002M) capable of over 346,795 measurements.

#### Features:

Auto-calibration of ON and OFF thresholds ensures reliable readings

User adjustable sensitivity control for low/high light level conditions

Optional light pipe eliminates effects of ambient sunlight or other lighting sources

# **Environment:**

The UX90-002 Data Logger is for use in Indoor environments

# **Supported Measurements:**

Light On/Off

Auto-calibration of ON and OFF thresholds ensures reliable readings

User adjustable sensitivity control for low/high light level conditions

Optional light pipe eliminates effects of ambient sunlight or other lighting sources


Replacement for: H06-002-02, U9-002

## **Internal Sensor**

Light Threshold: > 65 lux

Light Type: LED, CFL, fluorescent, HID, incandescent, natural

## Time



Plot A: Time Accuracy

**Accuracy**: ±1 minute per month at 25°C (77°F) (see

Plot A)

Battery Life: 1 year typical use

Memory:

UX90-002: 128 KB (84,650 measurements, maximum)

UX90-002M: 512 KB (346,795 measurements,

maximum)

Download Type: USB 2.0 interface

Download Time: 10 seconds for 128 KB; 30 seconds

for 512 KB

Logger Operating Range:

Logging: -20° to 70°C (-4° to 158°F); 0 to 95% RH

(non-condensing)

Launch/Readout: 0° to 50°C (32° to 122°F) per USB

specification

Launch/Readout: 0° to 50°C (32° to 122°F) per USB

specification

**LCD**: LCD is visible from: 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures

outside this range

**Size**: 3.66 x 5.94 x 1.52 cm (1.44 x 2.34 x 0.6 in.)

**Weight**: 23 g (0.81 oz)

**Environmental Rating**: IP50

• The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)

Email: info@tempcon.co.uk

Web site: www.tempcon.co.uk