



This product
complies with CE
directives

HOB0[®] Data Logger

S-LIA-M003 PAR Smart Sensor

The Photosynthetic Light (PAR) Smart Sensor is intended to measure light intensity for the frequencies relevant for photosynthesis. This sensor has a measurement range of 0 to 2500 $\mu\text{mol}/\text{m}^2/\text{sec}$ over wavelengths from 400 to 700 nm. Enclosed in a anodized aluminum housing with acrylic diffuser and o-ring seal, this model has a 3m cable; a light sensor bracket and light sensor level are recommended.

Measurement parameters: average over logging interval, user-defined sampling interval from 1 second

Measurement range: 0 to 2500 $\mu\text{mol}/\text{m}^2/\text{sec}$, wavelengths of 400 to 700 nm

Operating Temperature Range: -40° to 75°C (-40° to 167°F)

Accuracy: $\pm 5 \mu\text{mol}/\text{m}^2/\text{sec}$ or $\pm 5\%$, whichever is greater in sunlight; additional temperature-induced error $\pm 0.75 \mu\text{mol}/\text{m}^2/\text{sec}/\text{degree C}$ from 25°C. Cosine corrected 0 - 80 degrees, 360 degree rotation.

Resolution: 2.5 $\mu\text{mol}/\text{m}^2/\text{sec}$

Drift: $< \pm 2\%$ per year

Housing: anodized aluminum housing with acrylic diffuser and o-ring seal

Dimensions: 4.1 cm height x 3.24 cm diameter (1 5/8" height x 1 1/4" diameter)

Approximate Weight: 120 g (4 oz)

Cable Length: 3 meter (10')

Note: Light sensor bracket and light sensor level recommended

Order Information

Photosynthetically Active Radiation PAR Smart Sensor

Part No:

S-LIA-M003



Tempcon Instrumentation Ltd.
Unit 19, Ford Lane Business Park, Ford Lane
Ford, Nr. Arundel, West Sussex. BN18 0UZ
Tel: ++44 (0) 1243 558270 Fax: ++44 (0) 1243 558288
Email: info@tempcon.co.uk Web site: www.tempcon.co.uk

DW206
0909