

Measurement, Control, and Datalogging Solutions







PRESSURE-LEVEL PANORAMIQUE

REMOTE PANORAMIQUE

AMBIENT PANORAMIQUE

Panoramique Paper Recorders

Proven - Reliable - Portable

Panoramique mechanical, battery operated, paper-strip recorders are available with ranges and chart speeds to suit a wide range of applications in industry and research. Please consult our Sales Office to discuss your application

Ambient Panoramique (Temperature & Relative Humidity)

Paper-strip recording of temperature and relative humidity. Available with 1 or 2 channels.

- Temperature accuracy: ±1% of the MR with a minimum of ±0.5°C; RH: ±5% RH (at 23°C)
- Measurement ranges: -35°C+45°C; -25°C +30°C; 0°C+120°C; -100°C +50°C; -35°C+15°C;
 -35°C+15°C...
- Recording time: 24 hours, 7 days or 4x7 days; Recording medium: Pre-printed strip or roll
- Diagram movement: 2-speed quartz or mechanical clockwork; Power supply: battery 1.5V
- IP Rating: IP20; Fitted with a handle for easy transport.
- · Complete with battery, fibre-tip pen and manual

Remote Panoramique (Temperature)

Paper-strip recording of temperature.

The Remote Panoramique measures temperature of liquids or gas. Available with 1 or 2 channels.

- Temperature accuracy: ±3% of the MR with a minimum of ±2°C (at 23°C)
- Measurement range: -0°C+120°C; -30°C +30°C; -20°C+50°C; -0°C +75°C; -20°C +40°C
- Recording time: 24 hours, 7 days or 4x7 days; Recording medium: Pre-printed strip or roll
- Diagram movement: 2-speed quartz or mechanical clockwork; Power supply: battery 1.5V
- IP Rating: IP20; Fitted with a handle for easy transport.
- Complete with battery, fibre-tip pen and manual

Pressure-Level Panoramique (Pressure & Level)

The Panoramique Pressure / Level recorder measures the relative pressure, and level of liquids.

- Pressure accuracy: (from 0,6 B to 60 B): ± 1,5% of the MR; low pressure: ± 1,5% of the MR;
- Level accuracy: ± 1,5% of the MR
- Pressure Measurement range: 0mb to +40mb; 0mb to +60mb; 0mb to +100mb; 0mb to +250mb;
- Level Measurement range: 0 to 4m
- Available with 1 or 2 channels.
- Recording time: 24 hours, 7 days or 4x7 days; Recording medium: Pre-printed strip or roll
- Diagram movement : 2-speed quartz or mechanical clockwork; Power supply : battery 1.5V
- IP Rating: IP20; Fitted with a handle for easy transport.
- Complete with battery, fibre-tip pen and manual



Tempcon Instrumentation Ltd.
Unit 19, Ford Lane Business Park, Ford Lane
Ford, Nr. Arundel, West Sussex. BN18 0UZ
Tel: ++44 (0) 1243 558270 Fax: ++44 (0) 1243 558288
Email: info@tempcon.co.uk Web site: www.tempcon.co.uk