



West 4100+ 1/4 DIN Single Loop Temperature Controller

Product Images



Short Description

The West 4100+ is part of the Plus Series of controllers that take flexibility and ease of use to new levels.

The 4100+ controller is an evolved product from the N4100. The product benefits from having more versatile features and user-friendly functionalities such as remote setpoint inputs, digital inputs, plug-in output modules, a customisable operator/HMI menu, jumperless and auto-hardware configuration, and 24VDC transmitter power supply.

Please note, the price shown above is for the base unit without any configuration or additional options. Please ensure you select the appropriate configuration from the dropdown menus below in order to see the correct final price.

Description

The West 4100+ has been designed to incorporate improvements over the N4100 to save users' time (as much as 50% on product set-up), reduce inventory stock and virtually eliminate the likelihood of operator errors.

The 4100+ surpasses competitive offerings in terms of ease of use, delivery and value for money.

Key Features

- Dual setpoints with optional remote selection
- Plug-in output modules allow installing just the functions needed
- Expanded user-selectable operator modes
- User-selectable plug-and-play output cards
- Process and loop alarms
- Adjustable hysteresis
- Optional 10V SSR driver
- Optional analogue Remote Setpoint Input
- Improved Windows PC configuration software
- Improved easy to use HMI
- Jumperless input configuration
- Auto-hardware recognition
- Faster communication speeds
- More security options
- Backward compatible panel cut out, housing and terminal wiring capability.

Additional Information

Country of Manufacture	United Kingdom																																																																														
Product Category:	Single Loop Controller																																																																														
Dimensions and size:	96mm x 96mm x 100mm (HxWxD), 1/4 DIN																																																																														
Primary Input Type:	Universal (TC, RTD, DC linear mA/mV)																																																																														
Other Inputs:	Digital, Remote setpoint																																																																														
Output Type:	Relay, SSR, DC linear V or mA, Triac, 24V transmitter power supply																																																																														
Max. Number of Outputs:	3																																																																														
Control Type:	PID, ON/OFF, Manual, Alarm, Ramp to Setpoint																																																																														
Power Supply:	100-240V AC 50-60Hz, 20-48V AC 50/60 Hz, 22-65V DC																																																																														
Communications:	RS-485 serial (West ASCII or MODBUS®)																																																																														
Panel Sealing:	IP66																																																																														
Certifications:	CE, UL, ULC, CSA																																																																														
Software Tools:	Plus Series Configurator																																																																														
Ordering Code																																																																															
Explanation	<table border="0"> <tr> <td>Input Type</td> <td></td> <td>Option Slot B (not on 6100)</td> </tr> <tr> <td>3 Wire RTD or DC mV</td> <td>1</td> <td>0 Not fitted</td> </tr> <tr> <td>Thermocouple</td> <td>2</td> <td>1 Remote Setpoint Input (Full)</td> </tr> <tr> <td>DC mA</td> <td>3</td> <td>2 Display Colour</td> </tr> <tr> <td>DC Voltage</td> <td>4</td> <td>0 Red Upper & Lower</td> </tr> <tr> <td>Option Slot 1</td> <td></td> <td>1 Green Upper & Lower</td> </tr> <tr> <td>Not fitted</td> <td>0</td> <td>2 Red Upper, Green Lower</td> </tr> <tr> <td>Relay</td> <td>1</td> <td>3 Green Upper, Red Lower</td> </tr> <tr> <td>DC for SSR</td> <td>2</td> <td>Power Supply</td> </tr> <tr> <td>DC 0-10V</td> <td>3</td> <td>0 100-240V AC</td> </tr> <tr> <td>DC 0-20mA</td> <td>4</td> <td>2 24-48V AC or DC</td> </tr> <tr> <td>DC 0-5V</td> <td>5</td> <td>Option Slot A</td> </tr> <tr> <td>DC 2-10V</td> <td>6</td> <td>0 Not fitted</td> </tr> <tr> <td>DC 4-20mA</td> <td>7</td> <td>1 RS485 Communications</td> </tr> <tr> <td>Triac</td> <td>8</td> <td>3 Digital Input</td> </tr> <tr> <td>Option Slot 2</td> <td></td> <td>4 Remote Setpoint Input (Basic)</td> </tr> <tr> <td>Not fitted</td> <td>0</td> <td>Option Slot 3</td> </tr> <tr> <td>Relay</td> <td>1</td> <td>0 Not fitted</td> </tr> <tr> <td>DC Driver for SSR</td> <td>2</td> <td>1 Relay</td> </tr> <tr> <td>DC 0-10V</td> <td>3</td> <td>2 DC Driver for SSR</td> </tr> <tr> <td>DC 0-20mA</td> <td>4</td> <td>3 DC 0-10V</td> </tr> <tr> <td>DC 0-5V</td> <td>5</td> <td>4 DC 0-20mA</td> </tr> <tr> <td>DC 2-10V</td> <td>6</td> <td>5 DC 0-5V</td> </tr> <tr> <td>DC 4-20mA</td> <td>7</td> <td>6 DC 2-10V</td> </tr> <tr> <td>Triac</td> <td>8</td> <td>7 DC 4-20mA</td> </tr> <tr> <td></td> <td></td> <td>8 Transmitter Power Supply</td> </tr> </table>	Input Type		Option Slot B (not on 6100)	3 Wire RTD or DC mV	1	0 Not fitted	Thermocouple	2	1 Remote Setpoint Input (Full)	DC mA	3	2 Display Colour	DC Voltage	4	0 Red Upper & Lower	Option Slot 1		1 Green Upper & Lower	Not fitted	0	2 Red Upper, Green Lower	Relay	1	3 Green Upper, Red Lower	DC for SSR	2	Power Supply	DC 0-10V	3	0 100-240V AC	DC 0-20mA	4	2 24-48V AC or DC	DC 0-5V	5	Option Slot A	DC 2-10V	6	0 Not fitted	DC 4-20mA	7	1 RS485 Communications	Triac	8	3 Digital Input	Option Slot 2		4 Remote Setpoint Input (Basic)	Not fitted	0	Option Slot 3	Relay	1	0 Not fitted	DC Driver for SSR	2	1 Relay	DC 0-10V	3	2 DC Driver for SSR	DC 0-20mA	4	3 DC 0-10V	DC 0-5V	5	4 DC 0-20mA	DC 2-10V	6	5 DC 0-5V	DC 4-20mA	7	6 DC 2-10V	Triac	8	7 DC 4-20mA			8 Transmitter Power Supply
Input Type		Option Slot B (not on 6100)																																																																													
3 Wire RTD or DC mV	1	0 Not fitted																																																																													
Thermocouple	2	1 Remote Setpoint Input (Full)																																																																													
DC mA	3	2 Display Colour																																																																													
DC Voltage	4	0 Red Upper & Lower																																																																													
Option Slot 1		1 Green Upper & Lower																																																																													
Not fitted	0	2 Red Upper, Green Lower																																																																													
Relay	1	3 Green Upper, Red Lower																																																																													
DC for SSR	2	Power Supply																																																																													
DC 0-10V	3	0 100-240V AC																																																																													
DC 0-20mA	4	2 24-48V AC or DC																																																																													
DC 0-5V	5	Option Slot A																																																																													
DC 2-10V	6	0 Not fitted																																																																													
DC 4-20mA	7	1 RS485 Communications																																																																													
Triac	8	3 Digital Input																																																																													
Option Slot 2		4 Remote Setpoint Input (Basic)																																																																													
Not fitted	0	Option Slot 3																																																																													
Relay	1	0 Not fitted																																																																													
DC Driver for SSR	2	1 Relay																																																																													
DC 0-10V	3	2 DC Driver for SSR																																																																													
DC 0-20mA	4	3 DC 0-10V																																																																													
DC 0-5V	5	4 DC 0-20mA																																																																													
DC 2-10V	6	5 DC 0-5V																																																																													
DC 4-20mA	7	6 DC 2-10V																																																																													
Triac	8	7 DC 4-20mA																																																																													
		8 Transmitter Power Supply																																																																													
Brand	West																																																																														
Display Colour	Red, Green																																																																														
Display Digits	4																																																																														
Input Type	Thermocouple, RTD, Linear																																																																														
Typical applications	Industrial																																																																														
Measurements	Temperature, Universal																																																																														

Additional Options

Input Type	[1]3 Wire RTD or DC mV
	[2]Thermocouple
	[3]DC mA
	[4]DC Voltage
Option Slot 1	[0]Not Fitted
	[1]Relay Output
	[2]DC Drive Output for SSR
	[3]Linear 0-10V DC Output
	[4]Linear 0-20mA DC Output
	[5]Linear 0-5V DC Output
	[6]Linear 2-10V DC Output
	[7]Linear 4-20mA DC Output
	[8]Triac Output
Option Slot 2	[0]Not Fixed
	[1]Relay Output
	[2]DC Drive Output for SSR
	[3]Linear 0-10V DC Output
	[4]Linear 0-20mA DC Output
	[5]Linear 0-5V DC Output
	[6]Linear 2-10V DC Output
	[7]Linear 4-20mA DC Output
	[8]Triac Output
Option Slot 3	[0]Not Fitted
	[1]Relay Output
	[2]DC Drive Output for SSR
	[3]Linear 0-10V Output

	[4]Linear 0-20mA Output
	[5]Linear 0-5V Output
	[6]Linear 2-10V Output
	[7]Linear 2-10V Output
	[8]Transmitter Power Supply
Option Slot A	[0]Not Fitted
	[1]RS485 Serial Comms
	[3]Digital Input
	[4]Remote Setpoint Input (Basic)
Power Supply	[0]100-240V AC
	[2]24-48V AC or DC
Display Colour	[0]Red Upper & Lower
	[1]Green Upper & Lower
	[2]Red Upper, Green Lower
	[3]Green Upper, Red Lower
Option Slot B	[0]Not Fitted
	[R]Remote Setpoint Input (full, with secondary digital input)
Manual Language	[0]No Manual
	[1]English
	[2]French
	[3]German
	[4]Italian
	[5]Spanish
	[6]Chinese Mandarin
	[9]All European Languages (En/Fr/Gr/It/Sp) Concise Manuals
Packing Options	[0]Single Pack with Concise Manual
	[1]Bulk Pack with 1 Concise Manual per unit - Minimum 20 pcs

[2]Bulk Pack No Manual - Minimum 20 pcs

[3]Bulk Pack with 1 Full Manual per unit - Minimum 20 pcs

[5]Single Pack with 1 Full Manual per unit