



HOBO U12-015 Stainless Steel Data Logger

Product Images



Short Description

The HOBO U12 Stainless Temperature Data Logger is ideal for food, pharmaceutical, autoclave and other applications where high-accuracy temperature data is critical.

Description

The HOBO U12 Stainless Temperature Data Logger is ideal for food, pharmaceutical, autoclave, and other applications where high-accuracy temperature data is critical. With its broad temperature range (-40 to 125C) and food-grade stainless steel housing, the U12 Stainless Temperature Data Logger withstands process conditions from pasteurization to flash freezing and washdown. The U12 Stainless is also ideal for high-temperature or deep underwater applications.

Highlighted Features

- Food-grade 316 Series Stainless Steel

- High-accuracy, extended temperature range
- Suitable for high pressure applications to 2200psi
- Fast readout via direct USB interface
- Compatible with HOBOWare and HOBOWare Pro for logger setup, graphing and analysis

NOTE: HOBO loggers require a USB cable and [HOBOWare software](#) (free download).

Additional Information

Country of Manufacture	United States
Explanation	<p>Measurement range: -40° to 125°C (-40° to 257°F) Accuracy: ± 0.25°C from 0° to 50°C (± 0.45°F from 32° to 122°F), see Plot A in manual Resolution: 0.03°C at 25°C (0.05°F at 77°F), see Plot A Drift: 0.05°C/year + 0.1°C/1000 hrs above 100°C (0.09°F/year + 0.2°F/1000 hrs above 212°F) Response time in 1 m/s (2.2 mph) airflow U12-015: < 10 minutes, typical to 90% U12-015-02: 2.25 minutes, typical to 90% Response time in water U12-015: < 3.5 minutes, typical to 90% U12-015-02: 20 seconds, typical to 90% Time accuracy: ± 2 minute per month at 25°C (77°F), see Plot B in manual Operating environment: Air, water, steam, 0 to 100% RH Operating temperature Logging: -40° to 125°C (-40° to 257°F) Launch/readout: 0° to 50°C (32° to 122°F), per USB specification Battery life: 3 year typical use, factory replaceable Memory: 64K bytes (43,000 12-bit measurements) Construction: Food-grade 316 Series Stainless Steel Weight U12-015: 72 g (2.5 oz) U12-015-02: 82 g (2.9 oz) Logger dimensions: 17.5 x 101.6 mm (0.69 x 4.00 inches) Probe dimensions: (U12-015-02 only): 4 x 124 mm (0.16 x 4.90 inches) Pressure/depth rating: 2200 psi (1500 m/4900 ft) maximum Vibration rating: Navy spec: NAVMAT P-9492 (non-probe model only) The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).</p>
Brand	Onset HOBO
Channel(s)	1
Onset Product Series	U12
Typical applications	Environmental (Outdoor), Field Research, Food Safety, Pasteurization, Product Safety, Water Quality
Measurements	Temperature

Additional Options

Temperature Calibration Certificate	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)
HOBOWare Pro Software Options	HOBOWare Pro on USB Drive (USB cable included)
	HOBOWare Pro on CD (USB Cable Included)
	HOBOWare Pro - Download Only (USB cable NOT included)
USB Cable (included with HOBOWare Pro on USB Drive & CD)	HOBO U-Series to PC USB Cable