

Call our friendly team on +44 (0)1243 558270 Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 0UZ, UK www.tempcon.co.uk



# PM-80 Digital Manometer (HVAC)

### **Product Images**



# **Short Description**

Using measurement technology developed from the 2000 Series this Dual Input Digital Manometer offers good performance at an affordable price.

×

#### Description

Using measurement technology developed from the 2000 Series this Dual Input Digital Manometer offers good performance at an affordable price.

Specifically designed for engineers using twin tube connections, this Presure Meter (Manometer) is ideal for soundness testing and setting up boiler differential gas pressures. Manufactured from tough ABS plastic, this water-resistant instrument is supplied with a rubber boot to provide added protection during routine use. It can be magnetically attached for ease of use, and the back lit LCD allows easy viewing of the display in poor light conditions.

The PM series is a suitable replacement for the conventional U-tube, having a fast response coupled with high accuracy and at low cost.

#### **Key Features:**

- 0-130 mbar measurement
- 0.01 resolution up to 19.99 mbar, then auto switches to 0.1 resolution
- Measurement unit options (Selectable on the PM80 only)
- Differential Input 8mm tube connectors
- Water Resistant (IP67 rated)
- Rugged case with protective rubber boot
- Magnetic attachment or tilt stand
- Push button "Zero" and "Hold" features
- Backlit Digital Display
- Auto Power Off after 12 minutes

# **Additional Information**

Brand	Digitron
Range	0 - 130 mbar,
Typical applications	Building Performance, Environmental (Indoor), Environmental (Outdoor), HVAC
Measurements	Pressure