



HOBO H22-001 Energy Logger

Product Images



Short Description

The HOBO Energy Logger is a 15 channel, modular, flexible, reconfigurable logging system for applications in Energy, and Industrial monitoring applications.

Description

Monitor energy and industrial equipment with this 15-channel data logger (Part # H22-001). With multiple channels, energy and facility managers can quickly and easily detect and address a variety of issues relating to HVAC, machinery, and other systems. The HOBO H22-001 Energy Data Logger is modular and more economic than its alternatives because a toolbox full of data loggers is not necessary.

Deploy this product with a variety of pre-defined plug-and-play smart sensors to create a robust monitoring system. Compatible with HOBOWare® [software](#), researchers can conduct effective data analysis in minutes.

Highlighted Features

- Onset's most flexible data logger records up to 15 channels of over a dozen measurements
- Provides 12v excitation for third-party sensors
- Pre-configured smart sensors get you started fast
- Signal conditioning modules retain configurations until you change them, providing plug-and-play convenience for commonly used sensors
- Flexible power options include battery operation for AC power adapter

Additional Information

Country of Manufacture	United States
Explanation	<p>Operating range: -20° to 50°C (-4° to 122°F) with alkaline batteries -40° to 60°C (-40° to 140°F) with lithium batteries Sensor inputs: Three FlexSmart multi-channel modules and up to 6 Smart Sensors (which may have multiple parameters/channels) Sensor connectors: Six RJ-12 Smart Sensor jacks plus 3 FlexSmart module slots Communication: RS-232 via 3.5 mm serial port or/and 9-pin D-Sub connector Dimensions: 15.6 cm x 8.4 cm x 4.6 cm (6.13" x 3.31" x 1.81") Weight: 435 g (15.23 oz) with batteries 238 g (8.33 oz) without batteries Memory: 512K nonvolatile flash data storage Memory modes: Stop when full; wrap when full Operational indicators: Six indicators provide logging and sensor network status Logging interval: One second to 18 hours, user-specified interval (2-second minimum for two-channel S-FS-TRMSA operation) Sensor excitation: 12 V DC at 200 mA total, with user-programmable warmup time on a per-channel basis Battery life: One year typical use (up to 75 mA excitation with 10-minute or longer logging Interval and 1-second warmup time) External power: Supports optional 13.6 V DC regulated AC Wall Adapter Connector. Internal batteries may remain installed. Alternatively, an automotive battery or 9-12 V DC regulated Wall Adapter may be used, but it is recommended to remove the internal batteries since they will discharge to the level of the external supply. Time accuracy: 0 to 2 seconds for the first data point and ±5 seconds per week at 25°C (77°F) Logging mode: Immediate, timed delay, or trigger (button-push) start options; supports sampling intervals for some sensors Data communication: Current readings while logging; read out while logging; read out when stopped</p>
Brand	Onset HOBO
Battery type	Eight standard AA alkaline batteries included (for operating conditions -20°C/-4°F to 50°C/122°F); optional AA lithium batteries available for operating conditions of -40° to 60°C (-40° to 140°F).
Channel(s)	15
Onset Product Series	H22
Typical applications	Building Monitoring, Energy, Environmental (Indoor), HVAC

Measurements	4-20mA, Air Velocity, Amp Hour (Ah), CO2, Compressed Air Flow, Current AC, Current DC, Differential Pressure, Flow, Humidity, Kilowatts (kW), kWh, Power Factor (PF), Pressure, Pulse, Temperature, Universal, Volatile Organic Comp., Volt-Amp Reactive, Volt-Amp Reactive hour, Volt-Amps (VA), Voltage AC, Voltage DC, Watt Hours (Wh), Watts (W), Wind Direction, Wind Speed
--------------	--

Additional Options

HOBOWare Pro Software Options	HOBOWare Pro on USB Drive (USB cable included)
	HOBOWare Pro on CD (USB Cable Included)
	HOBOWare Pro - Download Only (USB cable NOT included)
USB Cable (included with HOBOWare Pro on USB Drive & CD)	HOBO U-Series to PC USB Cable