



## DISCONTINUED: HOBO 12-bit Temperature/Relative Humidity (8m cable) Smart Sensor

### Product Images



### Description

The HOBO 12-bit Temperature/Relative Humidity Smart Sensor is designed to work with all HOBO data

loggers that accept Smart Sensors. All sensor parameters are stored inside the Smart Sensor, which automatically communicates configuration data information to the logger without any programming, calibration, or extensive user setup.

## Key Features

- Smart Sensor
- Works with all loggers that accept Smart Sensor inputs
- Automatically communicates configuration data to the logger.

Also available in a [wireless model](#) for use with the [HOBOnet Field Monitoring System](#).

# Additional Information

Country of Manufacture	United States
Explanation	<p>The country of origin for this product is the United States. To see the full specifications for this product, please see the product manual found under the Resources tab.</p> <p><b>Measurement Range</b> Temp: -40°C to 75°C (-40°F to 167°F) RH: 0-100% RH at -40° to 75°C (-40° to 167°F); exposure to conditions below -20°C (-4°F) or above 95% RH may temporarily increase the maximum RH sensor error by an additional 1%</p> <p><b>Accuracy</b> Temp: +/- 0.21°C from 0° to 50°C (0.38°F from 32° to 122°F) RH: +/- 2.5% from 10% to 90% RH (typical), to a maximum of +/- 3.5% including hysteresis at 25°C (77°F); below 10% and above 90% ±5% typical</p> <p><b>Resolution</b> Temp: 0.02°C at 25°C (0.04°F at 77°F) RH: 0.1% RH</p> <p><b>Bits Per Sample</b> Temp: 12 RH: 10</p> <p><b>Drift</b> Temp: &lt; 0.1°C (0.18°F) per year RH: &lt; 1% per year typical</p> <p><b>Response Time (typical, to 90% of change)</b> Temp: 5 minutes in air moving 1 m/sec RH: 5 minutes in air moving 1 m/sec with protective cap</p> <p>Operating temperature range: -40°C to 75°C (-40°F to 167°F) Environmental rating weatherproof: 0 to 100% RH intermittent condensing environments. For best results, the Temp/RH Smart Sensor should be mounted inside a protective enclosure, such as a <a href="#">solar radiation shield</a>. Housing PVC cable jacket with ASA styrene polymer RH sensor cap; modified hydrophobic polyethersulfone membrane Sensor dimensions: 10 x 35 mm (0.39 x 1.39 in) Weight: 180 g (6.35 oz) Number of data channels: 2 Measurement averaging option: No Cable lengths available: 8 m (26.2 ft) Length of Smart Sensor network cable: 6 m (19.6 ft)</p> <p>This product meets CE specification EN61326 criterion C for ESD, criterion C for Radiated Immunity, criterion C for Fast Transient, criterion B for Conducted Immunity, criterion A for Power Frequency Magnetic Fields, and Radiated Emissions Group 1, Class B. To minimize measurement errors due to ambient RF, use the shortest possible probe cable length and keep the probe cable as far as possible from other cables.</p> <p><b>Note:</b> Sensor requires protection from rain or direct splashing; <a href="#">Radiation shield</a> strongly recommended for use in sunlight; sensors can be used in intermittent condensing environments up to 30°C and non-condensing above 30°C.</p>
Ideal For	Professional, Agronomy
Promotion	<b>This product has been replaced by the <a href="#">S-THC-M008</a></b>
Brand	Onset HOBO
Housing	Cable
Typical applications	Environmental (Indoor), Environmental (Outdoor), Weather Monitoring
Measurements	Dew Point, Humidity, Temperature
Compatible With	RX3000 Remote Monitoring Station Data Logger, RX2100 MicroRX Station, RX2100-WL MicroRX Water Level Station, U30-NRC U30 USB Weather Station Data Logger, H21-USB USB Micro Station Data Logger, H22-001 Energy Data Logger