



# DISCONTINUED: HOBO ZW-006 Wireless Data Node (4 x External Analog)

## Product Images



## Short Description

The HOBO® ZW-006 is a 4-channel wireless data node with four analog ports.

## Description

The HOBO® ZW-006 is a 4-channel wireless data node with four analog ports. It wirelessly transmits data in real time, reducing the costs and inconvenience associated with manual data offload.

## Highlighted Features

- Wirelessly transmits real-time data
- Compact size for easy deployment wherever data is needed
- Accepts a wide range of external energy and environmental sensors
- Notifies you of alarm conditions via email or text messages
- Onboard buffer memory helps prevent data loss
- Powerful HOBOWare® Pro software for organizing and viewing data (included with HOBOWare data receiver)

A complete system requires at least one wireless HOBOWare data node, [HOBOWare data receiver](#), and [HOBOWare Pro software](#) (included with [HOBOWare ZW-RCVR](#)). Depending on your system deployment, a [HOBOWare data router \(ZW-ROUTER\)](#) may be required.

# Additional Information

Country of Manufacture	United States
Explanation	<p>The country of origin for this product is the United States.</p> <p><b>Buffer memory:</b> 3k measurements</p> <p><b>Sample rate:</b> 1 min to 18 hrs</p> <p><b>Transmission rate:</b> 2 min and greater</p> <p><b>Power options:</b> AC power adapter, battery backup</p> <p><b>Measurement range analog channels:</b> 0 to 2.5 Vdc; 0 to 5 Vdc (w/CABLE-ADAP5); 0 to 10 Vdc (w/ CABLE-ADAP10); 4-20 mA (w/CABLE-4-20mA)</p> <p><b>Accuracy analog:</b> ± 1.544 mV plus 2 % (typical)</p> <p><b>Operating Range</b></p> <p><b>Temp:</b> -20 to 50°C (-4 to 122°F) when battery powered, -20 to 70°C (-4 to 158°F) when line powered.</p> <p><b>RH:</b> 5%-95% non-condensing</p> <p><b>Resolution:</b> Analog channel: 0.6mV</p> <p><b>Response time:</b> Dependent on sensor</p> <p><b>Range:</b> Approx. 100m (300ft.) depending on obstructions or interference</p> <p><b>Weight:</b> 138g (4.87 oz) with batteries</p> <p><b>Dimensions:</b> 96.5 x 108 x 28mm (3.8 x 4.25x 1.1 in)</p> <p><b>Radio power:</b> 1.6 mW (2 dBm)</p> <p><b>Wireless data standard:</b> IEEE802.15.4 2.4 GHz band</p> <p>CE - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)</p>
Promotion	<b>This product has been discontinued. See our full range of <a href="#">Data Loggers</a></b>
Brand	Onset HOBO
Channel(s)	4
Onset Product Series	ZW
Typical applications	Building Monitoring, Energy, Environmental (Indoor), Thermal Comfort
Measurements	4-20mA, Air Velocity, Amps (A), CO2, Compressed Air Flow, Current AC, Current DC, Differential Pressure, Kilowatts (kW), Pressure, Temperature, Voltage AC, Voltage DC

# Additional Options

HOBOWare Pro Software Options	HOBOWare Pro on USB Drive (USB cable included)
	HOBOWare Pro on CD (USB Cable Included)
	HOBOWare Pro - Download Only (USB cable NOT included)
USB Cable (included with HOBOWare Pro on USB Drive & CD)	HOBO U-Series to PC USB Cable