



DISCONTINUED: HOBO ZW-RCVR Wireless Data Node Receiver

Product Images



Short Description

The HOBO® data receiver collects incoming logged sensor data from HOBO data nodes and transfers the data to the computer via USB cable.

Description

The HOBO® data receiver collects incoming logged sensor data from HOBO data nodes and transfers the data to the computer via USB cable.

Highlighted Features

- Simple USB connection to PC
- Sends commands to HOBO data nodes as needed
- Retains all data node network parameters and settings

Price includes: HOBOWare® Pro software disc, mounting stand, USB connection cable, batteries, wall mounting accessories, setup guide, and power adapter.

Complete system requires a HOBO data receiver (ZW-RCVR) and one or more indoor wireless HOBO data nodes. Depending on your system deployment, a HOBO data router (ZW-ROUTER) may be required.

Additional Information

Country of Manufacture	United States
Explanation	<p>The country of origin for this product is the United States.</p> <p>Buffer Memory: up to 96k measurements</p> <p>Sample rate: N/A</p> <p>Transmission rate: N/A</p> <p>Operating Range</p> <p>Temp: -20 to 50°C (-4 to 122°F) when battery powered, -20 to 70°C (-4 to 158°F) when line powered.</p> <p>RH: 5%-95% non-condensing</p> <p>Power options: AC power adapter (Onset p/n AC-ZW-2 (US) or AC-ZW-3 (EU); via USB cabled to PC; (3) alkaline AAA batteries included.</p> <p>Range: Approx. 100 m (300 ft.) depending on obstructions or interference</p> <p>Weight: 138 g (4.87 oz.) w/ batteries</p> <p>Size: 96.5 x 108 x 28 mm (3.8 x 4.25 x 1.1 in.)</p> <p>Max # of Nodes Supported: 100</p> <p>Radio power: 1.6 mW (2 dBm)</p> <p>Wireless data standard - IEEE 802.15.4 2.4 GHz band</p> <p>CE - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)</p>
Promotion	This product has been discontinued. See our full range of Data Loggers
Brand	Onset HOBO
Channel(s)	100
Onset Product Series	ZW
Typical applications	Building Monitoring, Energy, Environmental (Indoor), Food Safety, Product Safety, Thermal Comfort
Measurements	4-20mA, CO2, Current AC, Humidity, Pulse, State, Temperature, Universal, Voltage AC, Voltage DC