Call our friendly team on Tempcon Instrumentation +44 (0)1243 558270 Ford Lane Business Park Ford West Sussex

> BN18 0UZ, UK www.tempcon.co.uk



# **Dickson SK4100 Chart Recorder - Temperature**

# **Product Images**





# **Short Description**

A great size (101mm), coupled with 2-3 year battery life makes the SK4100 temperature chart recorder a great monitoring solution.

# **Description**

A great size (101mm), coupled with 2-3 year battery life makes the SK4100 temperature chart recorder a great monitoring solution.

#### **Specifications:**

- 7-Day or 24-Hour recording
- C/F Switchable
- 2-3 year battery life
- Single AA battery operation
- Ambient Operating RH Conditions 0-95% RH non-condensing
- Ambient Operating Temperature Conditions -22 to 122F (-30 to 50C)
- Approvals CE
- Battery Life (Avg) 3 Years
- Calibration Options N100, N300, N400

- Channels CH1: Temperature
- Chart Rotation Speed 24 Hour or 7 Day
- Dimensions 2.4 x 5.2 x 5.2in
- Display Resolution 0.1
- Enclosure Black ABS and Polycarbonate
- IP Rating 21
- Included Accessories One AA Battery, Red Pen and Quick Start Guide. \*Charts sold separately.
- Mounting Options Free Standing or Wall Mounted
- Power Source Battery; One AA Battery (User Replaceable)
- Response Time 11 Minutes to 63% of Full Scale (in air moving 5' per second)
- Temperature Accuracy (Recorder Only) ± 2% Of Full Scale
- Temperature Range 0 to 100F (-18 to 37C)
- Temperature Sensor Precise spiral wound bi-metallic strip transducer
- Unit Weight 3 lbs
- Units/Pkg 1
- Warranty 12 Month Limited

### **Additional Information**

Brand	Dickson
Maximum Temperature	+37
Chart Size	101mm / 4in
Typical applications	Food Safety, HVAC, Thermal Processing
Measurements	Temperature