



Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 0UZ, UK www.tempcon.co.uk



PM-20 Series Pressure Meter (mbar)

Product Images





Short Description

Using measurement technology developed from the 2000 Series the PM range offers good performance at an affordable price.

Description

Using measurement technology developed from the 2000 Series the PM range offers good performance at an affordable price.

Specifically designed for engineers (Including HVAC) using twin tube connections, the PM range is ideal for soundness testing and setting up boiler differential gas pressures. Manufactured from tough ABS plastic, this water-resistant instrument is supplied with a rubber boot to provide added protection during routine use. It can be magnetically attached for ease of use, and the back lit LCD allows easy viewing of the display in poor light conditions.

Key Features:

- 0-130 mbar measurement
- 0.01 resolution up to 19.99 mbar, then auto switches to 0.1 resolution
- Differential Input 8mm tube connectors
- Water Resistant (IP67 rated)
- Rugged case with protective rubber boot
- Magnetic attachment or tilt stand
- Push button "Zero" and "Hold" features
- Backlit Digital Display
- Auto Power Off after 12 minutes
- Measurement unit options (Selectable on the PM80)

PM20 - mbar

Additional Information

Brand	Digitron
Range	0 - 130 mbar
Typical applications	Building Monitoring, Environmental (Indoor), Environmental (Outdoor), HVAC
Measurements	Pressure