

Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 OUZ, UK www.tempcon.co.uk




# DISCONTINUED: HOBO U12-015-03 Deep Ocean Temperature Logger

### **Product Images**







#### **Short Description**

The HOBO U12 Deep Ocean Water Temperature Logger is a single-channel water temperature logger with 12-bit resolution that can record up to 43,000 measurements. With its robust titanium housing, this logger is designed to withstand ocean extremes of depth and temperature.

## **Description**

The HOBO U12 Deep Ocean Water Temperature Data Logger is a single-channel water temperature logger with 12-bit resolution that can record up to 43,000 measurements. With its robust titanium housing, this logger is designed to withstand ocean extremes of depth and temperature.

#### **Highlighted Features**

• 11,000m depth rating (36,080 ft)

- Extended temperature range:- -40 to 125C
- Titanium housing for use in saltwater
- Fast readout via direct USB interface
- Compatible with HOBOware and HOBOware Pro software for logger setup, graphing and analysis

NOTE: HOBO loggers require a USB cable and HOBOware software (free download).

## **Additional Information**

Country of Manufacture	United States	
	Measurement Range:	-40° to 125°C (-40° to 257°F)
	Accuracy:	±0.22°C at 25°C (±0.4°F at 77°F), see Plot A in manual
	Resolution:	$0.025^{\circ}\text{C}$ at $25^{\circ}\text{C}$ ( $0.045^{\circ}\text{F}$ at $77^{\circ}\text{F}$ ), see Plot A in manual
Explanation	Drift:	0.05°C/year + 0.1°C/1000 hrs above 100°C (0.09°F + 0.2°F/1000 hrs above 212°F
	Response Time in Water:	< 4 minutes, typical to 90%
	Time Accuracy:	±2 minute per month at 25°C (77°F), see Plot B in manual
	Operating Environment:	Air, water, steam, 0 to 100% RH
	Operating Temperature:	Logging: -40° to 125°C (-40° to 257°F) Launch/Readout: 0° to 50°C (32° to 122°F), per USB specification
	Battery Life:	3 years typical use, factory replaceable
	Memory:	64K bytes (43,000 12-bit measurements)
	Construction:	Titanium with O-ring seals and backup rings
	Weight:	105 g (3.7 oz)
	Size:	114 x 20.6 mm diameter (4.5 x 0.81 in. diameter)
	Depth Rating:	11,000 m (36,080 ft)
	Pressure Rating:	1110 bar (16,000 psi)
	Vibration Rating:	Navy spec: NAVMAT P-9492
	×	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).
Promotion	This product has been superseded by the MX2204	
Brand	НОВО	
Channel(s)	1	
HOBO Product Series	U12	
Typical applications	Environmental (Outdoor)	
Measurements	Temperature, Water Temperature	

## Additional Options

HOBOware Pro Software Options	HOBOware Pro on USB Drive (USB cable included)
	HOBOware Pro on CD (USB Cable Included)
	HOBOware Pro - Download Only (USB cable NOT included)
Temperature Calibration Certificate	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)
USB Cable (included with HOBOware Pro on USB Drive & CD)	USB Cable for Data Logger to PC Communications (SKU: CABLE-USBMB)