



HOBO UX100-014M Thermocouple Data Logger

Product Images



Description

The HOBO UX100-014M Single Channel Thermocouple data logger records temperature in indoor environments with mini plug thermocouple sensors (sold separately).

Designed for a broad range of monitoring applications - from industrial process monitoring to concrete maturity testing - the data logger provides exceptional flexibility by accepting J, K, T, E, R, S, B or N type thermocouple probes.

- High-accuracy J, K, T, E, R, S, B, N thermocouple readings
- Easy-to view LCD display
- Large memory capacity
- Visual high & low alarm thresholds

- New Burst and Statistics logging modes

NOTE: HOBO loggers require a USB cable and [HOBOWare software](#) (free download).

Also available is the [HOBO UX120-014M](#) four-channel thermocouple data logger.

Additional Information

Country of Manufacture	United States
Explanation	The country of origin for this product is the United States. To see the full specifications for this product, please see the product manual found under the Resources tab.
	Thermocouple

Additional Options

Temperature Calibration Certificate	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)
HOBOWare Pro Software Options	HOBOWare Pro on USB Drive (USB cable included)
	HOBOWare Pro on CD (USB Cable Included)
	HOBOWare Pro - Download Only (USB cable NOT included)
USB Cable (included with HOBOWare Pro on USB Drive & CD)	HOBO U-Series to PC USB Cable