



# SPY RF U Wirelss Temperature Data Logger

## Product Images



## Short Description

Measurement range: from -200°C to +400°C/4-20mA/0-1V/ dry contact

# Description

Universal recorder (1 or 2 channels)

- Measurement range: from -200°C to +400°C/4-20mA/0-1V/ dry contact
- Measurement precision: ± 0,2°C from -20 to +50°C with probe and ±0.5°C out of the range
- Type of sensor: external (PT100. PT1000. 4-20mA, 0-1 V, contact)
- Protection index: IP65
- Used for all types of controlled temperature installations (-200°C to +400°C)
- Triggers a recording on channel 1 for any changes in the status of channel 2 (2 channel version only)
- Complies with EN 12 830, ROHS, CE, FCC, ETS 300-220
- Mixing of inputs possible on the 2 channel version
- Long-range radio: 1 km with open field
- Flexible recording interval (1s to 90 min)
- Internal memory: 10 000 measurements per channel
- Supplied with wall-mounting bracket and cable input protection
- Battery life: 2 years, interchangeable

Benefits:

- Monitors all types of temperature-controlled equipment (-200°C to +400°C)
- Possibility to have different types of input in 2-channel model (analogue or electrical)

# Additional Information

Brand	JRI
Maximum Temperature	+400
Channel(s)	2
Typical applications	Environmental (Indoor), Environmental (Outdoor)
Measurements	Temperature

# Additional Options

Number of Channels	1 Channel
	2 Channels