



# SPY RF N Wireless Digital Data Logger (T°/RH/Contact)

## Product Images



## Short Description

Wireless Digital recorder (T°/RH/contact)(1 or 2 channels)

# Description

Digital recorder (T°/RH/contact)(1 or 2 channels)

- Measurement range: T : -40 +80°C; TH: -30 +70°C and 0 to 100% RH
- Measurement precision: ± 0.3°C to -20 from 30°C and 0,5°C above and ±2% RH to 0 from 90%RH and ±3% to 90 from 100%RH (without probe)
- Type of sensor: external temperature, hygrometry and On/Off
- Protection index: IP65
- Fitted with interchangeable sensors for ease of maintenance
- Does not damage door seals (flat cable)
- Complies with EN 12830, ROHS, CE, FCC, ETS 300-220
- Long-range radio: 1 km with open field
- Internal memory: 10 000 measurements per channel
- Flexible recording interval (1s to 90 min)
- Supplied with wall fixing
- Battery life: 2 years, interchangeable

**Benefits:**

- Probes are interchangeable for easy maintenance
- Suitable for dry contact inputs
- Allows recording to start when a specific event occurs.
- Possibility to have different types of inputs on the 2 channels model (digital or electrical)

# Additional Information

Brand	JRI
Maximum Temperature	+80
Channel(s)	2
Typical applications	Building Monitoring, Cold Chain, Environmental (Indoor), Environmental (Outdoor)
Measurements	Humidity, State, Temperature

# Additional Options

Number of Channels	1 Channel
	2 Channels