



---

# DISCONTINUED: DicksonOne WFT25 WiFi Temperature Data Logger

## Product Images

---



## Short Description

---

DicksonOne automatically collects temperature and humidity data and delivers it to where you are. Easily set alarms and track trends without wasting time collecting charts or downloading data.

## Description

---

DicksonOne automatically collects temperature and humidity data and delivers it to where you are. Easily set alarms and track trends without wasting time collecting charts or downloading data. Let DicksonOne be proactive about your data so you don't have to!

### Features

- Access your data from any internet connected device, anywhere!

- Multiple locations - monitor 1 point or 1000's
- Scalable to any number of loggers
- Easy-to-use interface
- Email & SMS Text Alerts
- Secure Data
- Select Models are RS compatible

Explanation

### Specifications

- Alarm Type Audible
- Ambient Operating RH Conditions 0-95% RH non-condensing (Logger only)
- Ambient Operating Temperature Conditions -22 to 122F (-30 to 50C)
- Antenna Type External
- Approvals RoHS, FCC Part 15 Compliance, CE
- Battery Backup 4 AA Batteries
- Battery Life (Avg) 72 hours
- Calibration Options N100 , N300, N400, & N520
- Channels CH1: Temperature
- Data Capacity 32,000 (Backup)
- Digital Display Yes
- Dimensions 1.7 x 4.25 x 4.25in
- Download Type Wireless
- Enclosure Black; ABS Plastic Clam Shell
- IP Rating 21
- Included Accessories USB Cable, AC Adapter, 4 AA Batteries, RTD Probe
- Mounting Options Free Standing or Wall Mount (With Keyhole)
- Power Cord 6 ft
- Power Source 120 to 240 VAC, 12 VDC (INTL fittings available)
- Power Source Input AC 100-240 0.5V 60/50 Hz
- Power Source Output DC 9V, 1A
- Power Status Indicator Red/Green/Blue (RGB) LED
- Radio Frequency 2.4 GHz
- Remote Sensor Length 6 ft
- Remote Sensor Type 1 Platinum RTD Probe (Hard-Wired)
- Response Time 30 Seconds to 63% of Full Scale
- Sample Interval User Selectable from: 60 seconds, 90 seconds, 2 minutes, 5 minutes, 10 minutes, 30 minutes, 1 hour
- Signal Strength Less than 100 mW
- Storage Conditions -22 to 122F (-30 to 50C)
- Storage Conditions RH 0-95% RH non-condensing
- Temperature Accuracy +/-0.5F from -148 to 350F (+/-0.3C from -100 to 176C)
- Temperature Range -148 to 350F (-100 to 176C)
- Temperature Sensor Type Resistance Temperature Sensor
- Unit Weight 3 lbs
- Units/Pkg 1
- Wireless Range 300 ft line of sight

Note on Alarm Type Alarms can be created for scenarios where the readings are outside a given range, communication has been lost, or the batteries are low. All paid accounts are eligible to receive email and SMS text alarm notifications.

Promotion

**This product has been superseded by the [Dickson DWE WiFi and Ethernet Temp & Humidity Data Logger](#)**

Brand

Dickson