

Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 0UZ, UK www.tempcon.co.uk



Dickson PR150 Small Pressure Data Logger

Product Images







Short Description

The PR150 is a compact and discreet pressure data logger that fits in toolboxes, tight corners or in wide open spaces without attracting attention. The PR150 was built for real-world water and gas pressure monitoring.

Description

- NEW! USB Downloading
- 0-100 PSI (PSI, ATM, Bar, mBar, InH2O, FtH2O, mmH2O, mmHG, InHg, Pascal, kP, MCA)
- Water resistant case
- 3 year battery
- Pressure sensor includes built in diaphragm seal
- Delayed Start

Additional Information

Explanation	 Ambient Operating RH Conditions 0 to 100% RH Ambient Operating Temperature Conditions 22 to 122F (0 to 50C) Approvals CE Battery Life (Avg) 1 Year at 5 minute sample rate (also dependent on operating environment) Calibration Options N100, N300 Data Capacity 32512 Delayed Start Yes Dimensions 2 x 2 x 2inches (58 x 58 x 58cm) Download Time 45 Seconds Download Type USB Enclosure Water Resistant Stainless Steel Fitting 1/4" NPT Thread, 5/8" Hex (Sensor includes built-in Diaphragm Seal) IP Rating 65 Included Accessories One 3.6 V Lithium Battery and Quick Start Guide. *Software sold separately. Minimum Software Version Required 17.16 PC Requirements Microsoft Windows 98 or newer, 4 MB RAM, 1 free COM (serial) port, CD drive Power Source 3.6 V Lithium Battery (User Replaceable); Battery Pressure Accuracy 1% Pressure Range 0 to 100PSI Sample Interval User Selectable (from 10 seconds to 24 hour intervals, in 10 second increments). Unit Weight 1 lb Units of Measure PSI, ATM, Bar, mBar, InH2O, FtH2O, mmH2O, mmHG, InHg, Pascal, kP, MCA Units/Pkg 1 Warranty 12-Month Limited
Brand	Dickson
Typical applications	Building Monitoring, HVAC, Industrial
Measurements	Pressure

Additional Options

Software (required to setup your Dickson loggers, view and download data) DicksonWare Software