



West Digital Timer ETM2432

Product Images



Short Description

The ETM2432 is fully adjustable with nine timer modes and designed for easy integration within a control installation to fit the user's needs.

Description

The ETM2432 is fully adjustable with nine timer modes and designed for easy integration within a control installation to fit the user's needs.

- Dual contact timed output
- External start, reset and hold digital inputs
- Start/stop/reset control from front panel
- HH:MM or MM:SS
- Scale 0:01 to 99:59 minutes / 0:01 to 99:59 hours

- Adjustable increasing and decreasing steps
- Time remaining displayed
- Upper and lower adjustable timer limits
- Audible tones

Product Category:	Timer
Supply voltage:	230V AC \pm %10, 50/60Hz or 9-30V DC/7-24V AC, 50/60Hz
Display:	4 digits, 12.5mm, 7 segment LED
Input:	Start, reset gate: Mechanical contact (minimum 50ms)
Output:	Out : 2 relays: 250V AC, 8A (for resistive load), NO and NC control output. Life expectancy for relays : 30.000.000 switching for no-load operation; 300.000 switching for 8A resistive load at 250V AC
Dimensions:	W77xH35xD61mm
Safety requirements:	EN 61010-1: 2010 (Pollution degree2 , overvoltage category II)
EMC:	EN 61326-1: 2006 (Performance criterion B is satisfied for EN 610000-4-3)
Protection class:	According to EN 60529; Front panel: IP65 Rear panel: IP20

BUYING IN BULK, OR JUST WANT SOME HELPFUL ADVICE?

Call **+44 (0)1243 558270**, click on the webchat box below, or fill out our [contact form](#).

Additional Information

Country of Manufacture	Türkiye
Brand	West
Display Colour	Red
Display Digits	4 digits, 12.5mm, 7 segment LED
Input Type	Start, reset gate: Mechanical contact (minimum 50ms)

Additional Options

Power Supply Input	[230] 230VAC
	[SM] 9-30VDC / 7-24VAC