



Call our friendly team on +44 (0)1243 558270

Tempcon Instrumentation

Ford Lane Business Park

Ford

West Sussex

BN18 0UZ, UK



on.co.uk

---

# **HOBO MX2302A Wireless Temperature and Humidity Data Logger with External Sensor - Optional Remote Monitoring**

## Product Images

---



## Short Description

---

This data logger from Onset is designed to withstand harsh indoor/outdoor conditions.

## Description

---

The HOBO MX2302A is a weatherproof data logger with external temperature and relative humidity sensors. Leveraging Bluetooth Low Energy, the logger enables easy, fast set up and data download directly from your mobile device. For remote cloud-based access to your data and alerts, simply add the optional [MX Gateway](#).

## Key Features

- Convenient wireless setup and data download via Bluetooth Low Energy, or via the cloud with the optional MX Gateway
- View current data in real time with the free HOBOnnect app, and near real-time cloud-based monitoring with the optional MX Gateway
- Receive alert notifications for out-of-range conditions via email or SMS text message with the optional MX Gateway
- Visual alerts on the data logger and app
- Retrieve data in hard-to-reach locations
- Compact, weatherproof housing with built-in mounting system
- Share downloaded data easily from your mobile device
- Accuracy: +/- 0.2C° and +/- 2.5% RH.



# Additional Information

Country of Manufacture	United States		
Brand	Onset HOBO		
Measurements	Humidity, Temperature		
Typical applications	Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety		
Onset Product Series	MX2300		
Explanation	<b>Features:</b> <ul style="list-style-type: none"><li>• Convenient wireless setup and download via Bluetooth Low Energy (100-foot range)</li><li>• Retrieve data in hard-to-reach locations</li><li>• Visual alarms alert you to out-of-range conditions</li><li>• Compact, weatherproof housing with built-in mounting</li><li>• View current data in real time with Onset's free HOBOnnect app</li><li>• Share downloaded data easily from your mobile device</li><li>• Accuracy: +/- 0.2C° and +/- 2.5% RH</li></ul>		
Power	Battery Only		
Sensors	<b>Temperature Sensor:</b>		
	Range	MX2301A and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302A external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year	
	Accuracy	±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only	
	Resolution	0.04°C (0.072°F)	
	Drift	<0.01°C (0.018°F) per year	
	<b>RH Sensor:</b>		
	Range	0 to 100% RH, -40° to 70°C (-40° to 158°F); exposure to conditions below -20°C (-4°F) or above 95% RH may temporarily increase the maximum RH sensor error by an additional 1%	
	Accuracy	±2.5% from 10% to 90% (typical) to a maximum of ±3.5% including hysteresis at 25°C (77°F); below 10% RH and above 90% RH ±5% typical	
	Resolution	0.01%	
	Drift	<1% per year typical	Memory
Dimensions	Logger housing: 10.8 x 5.08 x 2.24 cm. External temperature sensor diameter: 0.53 cm. External temperature/RH sensor diameter: 1.17 cm. External sensor cable length: 2 m. Solar radiation shield bracket: 10.8 x 8.3 cm		
Batteries	2/3 AA 3.6 volt lithium, user replaceable		
Power	Battery only		

# Additional Options

<b>Optional Remote Cloud Access to Your Data</b>	MX Gateway for HOBO MX Data Loggers (SKU: MXGTW1)
	HOBOLink Service Plan (One Year Subscription (SKU: SP-620)) - one required per MX Gateway
<b>Temperature &amp; Humidity Calibration Certificate</b>	Temperature & Humidity Calibration @ 20°C and 50RH
	Temperature & Humidity Calibration (please specify measurement points required)