



HOBO MX2201 Bluetooth Waterproof (30 Metres) Temperature Data Logger

Product Images



Short Description

Delivers accurate temperature measurements straight to your iOS or Android mobile device, and is ideal for

measuring temperature in streams, lakes, oceans, and soil environments.

Description

The HOBO MX2201 waterproof temperature/light level logger leverages the power of Bluetooth Low Energy (BLE) to deliver accurate temperature measurements straight to your mobile device or Windows computer with the free HOBOnnect app. Designed for durability, this compact waterproof logger is ideal for measuring temperature in streams, lakes, oceans, and soil environments. Data collection in the field has never been easier!

Key Features

- Convenient wireless setup and download via Bluetooth Low Energy (BLE)
- Large memory stores 96,000 measurements
- Waterproof to 30 metres (100 feet)
- User-replaceable battery
- Mounting tabs for fast, easy deployment
- LED alarm notifies you when temperature exceeds set threshold
- $\pm 0.5^{\circ}\text{C}$ ($\pm 0.9^{\circ}\text{F}$) temperature accuracy
- Mounting boot included

Operates in indoor, outdoor and underwater environments.

Supports the following measurements: Soil Temperature, Temperature and Water Temperature.

Requires a compatible mobile device or Windows computer and the free HOBOnnect app.

Access your data directly from your mobile phone, tablet, or Windows computer when within 100 foot line-of-sight range of the logger - with the free HOBOnnect app.

To enable [cloud data storage](#) and analysis - add an [MX Data Plan](#) (select from options above).

To enable near real-time remote monitoring and alerts via email/text message - add an MX Data Plan [and](#) [MX Gateway](#) (select options above). Note: The MX Gateway must be indoors.

You can download the HOBOnnect app here



Additional Information

Country of Manufacture	United States
Explanation	Temperature Sensor (MX2201)
	Range -20° to 70°C (-4° to 158°F) in air -20° to 50°C (-4° to 122°F) in water
	Accuracy ±0.5°C from -20° to 70°C (-4° to 158°F)
	Resolution 0.04°C (0.072°F)
	Drift <0.1°C (0.18°F) per year
	Response Time 17 minutes typical to 90% in air moving 1 m/s, unmounted 7 minutes typical to 90% in stirred water, unmounted
	Logger
	Radio Power 1 mW (0 dBm)
	Transmission Range Approximately 30.5 m (100 ft) line-of-sight
	Wireless Data Standard Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)
	Logger Operating Range -20° to 70°C (-4° to 158°F) in air
	Logging Rate 1 second to 18 hours
	Buoyancy (Fresh Water) 2g (0.07 oz) positive
	Waterproof To 30.5 m (100 ft)
	Memory 96,000 measurements
	Battery CR2032 3V lithium, user replaceable
	Battery Life 1 year typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always Off disabled in software. 2 years typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always Off enabled in software. Faster logging intervals and statistics sampling intervals, burst logging, remaining connected with the app, excessive downloads, and paging may impact battery life. To ensure proper battery installation, see Battery Information for detailed instructions on replacing the battery.
	Time Accuracy ± 1 minute per month at 25°C (77°F)
	Full Memory Download Approximately 45 seconds; may take longer the farther the device is from the logger
	Wetted Materials Polypropylene case, EPDM O-ring
	Dimensions 3.35 x 5.64 x 1.6 cm (1.32 x 2.22 x 0.63 inches)
	Weight 12.75 g (.45 oz)
	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU). This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.
Contents	Data Logger, Protective Boot
Ideal For	Professional, Education
Brand	HOBO
HOBO Product Series	Pendant (UA)
Typical applications	Building Monitoring, Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety, Water Quality
Measurements	Temperature, Water Temperature

Optional cloud data storage and analysis - select an annual MX Data Plan from the options below (one Data Plan required per logger)	MX-Speed (Supports up to 4 measurements with 1 minute logging)
	MX-Data (Supports up to 10 measurements with 5 minute logging)
Optional near real-time remote monitoring and alerts via email/text message (requires an MX Gateway, plus one MX Data Plan for each MX Logger)	MX Gateway for HOBO MX Data Loggers (SKU: MXGTW1)
Temperature Calibration Certificate	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)