



HOBO MX2201 Bluetooth Waterproof (30 Metres) Temperature Data Logger

Product Images



Short Description

Delivers accurate temperature measurements straight to your iOS or Android mobile device, and is ideal for

measuring temperature in streams, lakes, oceans, and soil environments.

Description

The HOBO MX2201 waterproof temperature/light level logger leverages the power of Bluetooth Low Energy (BLE) to deliver accurate temperature measurements straight to your mobile device with Onset's free HOBOnnect app. Designed for durability, this compact waterproof logger is ideal for measuring temperature in streams, lakes, oceans, and soil environments. Data collection in the field has never been easier!

For remote cloud-based access to your data and alerts via email/SMS text message, simply add the optional [MX Gateway](#) (indoor deployments).

Key Features

- Convenient wireless setup and download via Bluetooth Low Energy (BLE)
- Large memory stores 96,000 measurements
- Waterproof to 30 metres (100 feet)
- User-replaceable battery
- Mounting tabs for fast, easy deployment
- LED alarm notifies you when temperature exceeds set threshold
- Works with Onset's free HOBOnnect app
- $\pm 0.5^{\circ}\text{C}$ ($\pm 0.9^{\circ}\text{F}$) temperature accuracy.

Operates in indoor, outdoor and underwater environments.

Supports the following measurements: Soil Temperature, Temperature and Water Temperature.

Additional Information

| | |
|------------------------|---|
| Country of Manufacture | United States |
| Explanation | Temperature Sensor (MX2201) |
| | Range -20° to 70°C (-4° to 158°F) in air -20° to 50°C (-4° to 122°F) in water |
| | Accuracy ±0.5°C from -20° to 70°C (-4° to 158°F) |
| | Resolution 0.04°C (0.072°F) |
| | Drift <0.1°C (0.18°F) per year |
| | Response Time 17 minutes typical to 90% in air moving 1 m/s, unmounted 7 minutes typical to 90% in stirred water, unmounted |
| | Logger |
| | Radio Power 1 mW (0 dBm) |
| | Transmission Range Approximately 30.5 m (100 ft) line-of-sight |
| | Wireless Data Standard Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0) |
| | Logger Operating Range -20° to 70°C (-4° to 158°F) in air |
| | Logging Rate 1 second to 18 hours |
| | Buoyancy (Fresh Water) 2g (0.07 oz) positive |
| | Waterproof To 30.5 m (100 ft) |
| | Memory 96,000 measurements |
| | Battery CR2032 3V lithium, user replaceable |
| | Battery Life 1 year typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always Off disabled in software. 2 years typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always Off enabled in software. Faster logging intervals and statistics sampling intervals, burst logging, remaining connected with the app, excessive downloads, and paging may impact battery life. To ensure proper battery installation, see Battery Information for detailed instructions on replacing the battery. |
| | Time Accuracy ± 1 minute per month at 25°C (77°F) |
| | Full Memory Download Approximately 45 seconds; may take longer the farther the device is from the logger |
| | Wetted Materials Polypropylene case, EPDM O-ring |
| | Dimensions 3.35 x 5.64 x 1.6 cm (1.32 x 2.22 x 0.63 inches) |
| | Weight 12.75 g (.45 oz) |
| | The CE Marking identifies this product as complying with all relevant directives in the European Union (EU). This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. |
| Contents | Data Logger, Protective Boot |
| Ideal For | Professional, Education |
| Brand | Onset HOBO |
| Onset Product Series | Pendant (UA) |
| Typical applications | Building Monitoring, Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety, Water Quality |
| Measurements | Temperature, Water Temperature |

Additional Options

| | |
|---|---|
| Optional Remote Cloud Access to Your Data | MX Gateway for HOBO MX Data Loggers (SKU: MXGTW1) |
| | HOBOLink Service Plan (One Year Subscription (SKU: SP-620)) - one required per MX Gateway |
| Temperature Calibration Certificate | 2 Point Temperature Calibration (0°C / 60°C) |
| | 2 Point Temperature Calibration (please specify temperature points) |
| | 1 Point Temperature Calibration (0°C) |