

Call our friendly team on +44 (0)1243 558270 Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 OUZ, UK www.tempcon.co.uk



Dickson RS081 Replaceable Differential Pressure Sensor (0.5")

Product Images





Short Description

Available Units of Measure: mm Hg, Pascales, PSI, inH20. Intended for use with the Dickson TSB, TWE, TWP, DWE data loggers.

Description

Available units of measure: mm Hg, Pascales, PSI, inH20.

Replaceable Sensors make calibration a smooth and simple process: when your data logger is due for

calibration, simply order the appropriate Replaceable Sensor with the type of calibration you need. When you receive the new sensor, detach the old one, replace it with the new one, and then . . . you're done!

The RS081 is intended for use with the following DicksonOne data loggers: TSB, TWE, TWP, DWE.

If installing a new Dickson Differential Pressure monitoring unit, you may need a may need a Differential Pressure Accessory Kit to ensure proper installation.

Additional Information

Brand	Dickson
Explanation	Differential Pressure Accuracy +/-3.0% from -0.5 to 0.5inH20 Resolution 0.000 Note: Current TWE / TWP / TSB will need V2.1.28; DWE needs V1.5.5
Measurements	Differential Pressure

Additional Options

Accessory Kit	A794 Differential Pressure Accessory Kit
Pressure Calibration Certificate	Pressure Calibration (Contact us for a quotation)