



Lowell Instruments TCM-5 10Km Very Deep Ocean Tilt Current Meter

Product Images



Short Description

Tilt Current Meters measure current using the drag-tilt principle. The physical design is simple; the meter is buoyant and is secured by a flexible tether to a fixed anchor or tripod. Moving water tilts the logger in the direction of flow. A 3-axis accelerometer and 3-axis magnetometer determine tilt and bearing. The meter also contains a thermistor for recording temperature.

Description

10,000 Meter Depth Rated Current Meter for the Very Deep Ocean

The Lowell Instruments TCM-5 Tilt Current Meter records water velocity in an affordable, easy-to-use package. The meter is designed for use beyond the edge of the continental shelf up to 10,000 meters depth. It is easy to deploy with a simple ground anchor from a remotely operated vehicle or attached to a benthic lander.

Key Features

Relatively Low Cost	Water velocity measurements for a fraction of the cost of an equivalent depth acoustic meter
10,000m Depth Rating	Operate almost everywhere in the deep ocean
Rugged Construction	Titanium pressure housing with toughened syntactic foam flotation
Long Battery Life	1-minute velocity sampling for more than 1 year
Large Memory	microSD memory card virtually eliminates memory concerns
Temperature Sensor	Includes an internal thermistor accurate to <0.1 °C with resolution of < 0.01 °C
USB 2.0 Interface	Connect with standard USB cables

Additional Information

Country of Manufacture	United States																																																				
Explanation	<p>Tilt Current Meters measure current using the drag-tilt principle. The physical design is simple; the meter is buoyant and is secured by a flexible tether to a fixed anchor or tripod. Moving water tilts the logger in the direction of flow. A 3-axis accelerometer and 3-axis magnetometer determine tilt and bearing. The meter also contains a thermistor for recording temperature.</p> <p>The meter's electronics are housed in a titanium pressure case with no external sensors. The floatation is derived from toughened syntactic foam. The built-in data logger includes a USB communication interface, a microSD flash memory card, and a long-life lithium battery. Windows® software is used to configure the TCM-5 for deployment and to process data.</p> <p>The TCM-5 is available at a fraction of the cost of similar depth capable acoustic meters and is simple to setup and deploy. The low total cost permits multiple current meters to be deployed in many locations simultaneously, thereby increasing spatial data density and reducing uncertainty.</p> <p>The core of the TCM-5 is the MAT-1 Data Logger. The MAT-1 data logger was designed for NOAA and is ideally suited as the "brains" of a tilt current meter.</p>																																																				
	<p>Specifications</p> <table border="1"> <thead> <tr> <th></th> <th>Range</th> <th>Accuracy</th> <th>Resolution</th> </tr> </thead> <tbody> <tr> <td>Speed (Low Range)</td> <td>0-50 cm/s</td> <td>3 cm/s + 3% of reading</td> <td>0.1 cm/s</td> </tr> <tr> <td>Speed (High Range)</td> <td>0-75 cm/s</td> <td>Not specified</td> <td>0.1 cm/s</td> </tr> <tr> <td rowspan="2">Direction</td> <td>0-360°</td> <td>5° (for speed >5 cm/s)</td> <td>0.1°</td> </tr> <tr> <td>-5 to 30 °C</td> <td>0.1 °C</td> <td><0.005 °C</td> </tr> <tr> <td rowspan="2">Temperature</td> <td>-20 to -5, 30 to 50°C</td> <td>0.2 °C</td> <td><0.01 °C</td> </tr> </tbody> </table> <p>Electronics</p> <table border="1"> <tbody> <tr> <td>Memory</td> <td>8 GB microSDHC flash card (standard)</td> </tr> <tr> <td>Communications</td> <td>Full speed USB micro-B port</td> </tr> <tr> <td>Battery Type</td> <td>3.6 V, size A, user replaceable lithium (from Lowell Instruments)</td> </tr> <tr> <td>Battery Life</td> <td>Months to years depending on recording rates</td> </tr> <tr> <td>Internal Clock</td> <td>< 1 minute of per month</td> </tr> </tbody> </table> <p>Operating Modes</p> <table border="1"> <tbody> <tr> <td>Start and Stop</td> <td>Start and Stop at user defined times</td> </tr> <tr> <td>Burst Mode</td> <td>Variable rate logging at user defined interval</td> </tr> <tr> <td>Recording Rate</td> <td>Current: 64 Hz to 1 sample per hour Temperature: 1 Hz to 1 sample per hour</td> </tr> </tbody> </table> <p>Mechanical</p> <table border="1"> <tbody> <tr> <td>Depth Rating</td> <td>10,000 m, housing tested to 13,700m</td> </tr> <tr> <td>Dimensions</td> <td>Flotation Diameter: 5.08 cm (2.00") Pressure Housing Diameter: 2.54 cm (1.00") Overall Length: 109 cm (43") Flotation Length: 91.4 cm (36.0")</td> </tr> <tr> <td>Weight</td> <td>1.86 Kg (4.09 lb)</td> </tr> <tr> <td>Construction</td> <td>Flotation: Toughened Syntactic Foam Pressure Housing: Titanium TI-6AL-4V, Double Buna O-ring seal with backup rings.</td> </tr> </tbody> </table> <p>Software</p> <table border="1"> <tbody> <tr> <td>User Interface</td> <td>Windows® Compatible Software Download</td> </tr> <tr> <td>USB</td> <td>USB 2.0 compliant MSC and CDC Classes</td> </tr> <tr> <td>Firmware</td> <td>Field upgradable via USB cable</td> </tr> </tbody> </table>		Range	Accuracy	Resolution	Speed (Low Range)	0-50 cm/s	3 cm/s + 3% of reading	0.1 cm/s	Speed (High Range)	0-75 cm/s	Not specified	0.1 cm/s	Direction	0-360°	5° (for speed >5 cm/s)	0.1°	-5 to 30 °C	0.1 °C	<0.005 °C	Temperature	-20 to -5, 30 to 50°C	0.2 °C	<0.01 °C	Memory	8 GB microSDHC flash card (standard)	Communications	Full speed USB micro-B port	Battery Type	3.6 V, size A, user replaceable lithium (from Lowell Instruments)	Battery Life	Months to years depending on recording rates	Internal Clock	< 1 minute of per month	Start and Stop	Start and Stop at user defined times	Burst Mode	Variable rate logging at user defined interval	Recording Rate	Current: 64 Hz to 1 sample per hour Temperature: 1 Hz to 1 sample per hour	Depth Rating	10,000 m, housing tested to 13,700m	Dimensions	Flotation Diameter: 5.08 cm (2.00") Pressure Housing Diameter: 2.54 cm (1.00") Overall Length: 109 cm (43") Flotation Length: 91.4 cm (36.0")	Weight	1.86 Kg (4.09 lb)	Construction	Flotation: Toughened Syntactic Foam Pressure Housing: Titanium TI-6AL-4V, Double Buna O-ring seal with backup rings.	User Interface	Windows® Compatible Software Download	USB	USB 2.0 compliant MSC and CDC Classes	Firmware
	Range	Accuracy	Resolution																																																		
Speed (Low Range)	0-50 cm/s	3 cm/s + 3% of reading	0.1 cm/s																																																		
Speed (High Range)	0-75 cm/s	Not specified	0.1 cm/s																																																		
Direction	0-360°	5° (for speed >5 cm/s)	0.1°																																																		
	-5 to 30 °C	0.1 °C	<0.005 °C																																																		
Temperature	-20 to -5, 30 to 50°C	0.2 °C	<0.01 °C																																																		
	Memory	8 GB microSDHC flash card (standard)																																																			
Communications	Full speed USB micro-B port																																																				
Battery Type	3.6 V, size A, user replaceable lithium (from Lowell Instruments)																																																				
Battery Life	Months to years depending on recording rates																																																				
Internal Clock	< 1 minute of per month																																																				
Start and Stop	Start and Stop at user defined times																																																				
Burst Mode	Variable rate logging at user defined interval																																																				
Recording Rate	Current: 64 Hz to 1 sample per hour Temperature: 1 Hz to 1 sample per hour																																																				
Depth Rating	10,000 m, housing tested to 13,700m																																																				
Dimensions	Flotation Diameter: 5.08 cm (2.00") Pressure Housing Diameter: 2.54 cm (1.00") Overall Length: 109 cm (43") Flotation Length: 91.4 cm (36.0")																																																				
Weight	1.86 Kg (4.09 lb)																																																				
Construction	Flotation: Toughened Syntactic Foam Pressure Housing: Titanium TI-6AL-4V, Double Buna O-ring seal with backup rings.																																																				
User Interface	Windows® Compatible Software Download																																																				
USB	USB 2.0 compliant MSC and CDC Classes																																																				
Firmware	Field upgradable via USB cable																																																				
Contents	<ul style="list-style-type: none"> • TCM-5 Tilt Current Meter • Lithium battery (installed in logger) • 8 GB microSD card (installed in data logger) • 1 m (3 ft) USB A to micro-B Cable • 2 spare set of O-rings, backup rings and lubricant • 30 cm (12") lanyard • microSD-to-SD card adapter 																																																				
Brand	Lowell Instruments																																																				
Typical applications	Datalogging																																																				
Measurements	Water Flow																																																				