



M3 Countertop Medical Fridge (23 Litre) - Optional Temperature Data Logger

Product Images



Note: Shown with optional glass door
(supplied as standard with solid door)



Short Description

Made in the UK for safe and efficient refrigerated storage of drugs and vaccines. High / low temperature alarms and optional temperature data logging.

Description

This medical fridge is made in the UK to the highest standards and is designed for safe and efficient refrigerated storage of drugs and vaccines.

The M3 model features high / low temperature alarms and optional data logging, for safe drug and vaccine storage. The exterior is white with a green lid section to highlight its purpose, and the door is fitted with an antimicrobial copper handle. The interior is 304 grade stainless steel (harder wearing than moulded plastic), with wire shelves to maintain airflow for even temperature distribution.

With the optional [CX402 temperature data logger](#) and [CX Internet Gateway](#), you can get remote alert notifications of temperature excursions and automatically download data from loggers within range of the device.

Key Features: M3 Medical Fridge

- Ideal for vaccine refrigerated storage
- 1°C to 5°C standard temperature range (can be altered to suit specific requirements)
- Fan-assisted interior for even temperature distribution
- Front vented and needs minimal airspace around it (20mm recommended above)
- Maintenance-free condenser & auto-defrost
- LED lighting and low-voltage fans for low energy consumption
- Digital temperature controller
- High / low temperature alarms
- Data logging facility optional
- Solid lockable door standard / glass lockable door optional
- Antimicrobial copper door handle
- Interior is 304 grade stainless steel (harder wearing than moulded plastic)
- Uses environmentally-friendly R600a hydrocarbon refrigerant
- Rear rollers for easy moving to clean.

Key Features: Optional CX402 Temperature Data Logger

- Easy-to-read display with current and daily min/max temperatures
- Audible and visual alarms
- Bluetooth transmission of data and alarm states
- Logger setup and download of data in seconds – without a PC or cable
- +/- 0.5°C accuracy for reliable temperature readings
- Battery-powered to guard against local power loss
- Optional ISO 17025 compliant calibration (NIST included)
- Used in conjunction with the InTemp app, easily view data plus create & share secure PDF reports for streamlined reporting and regulatory compliance.

Explanation	DIMENSIONS	
	Height	560 mm
	Width	350 mm
	Depth	520 mm
	Capacity	23 litre
	Weight: 24 kg	
	OTHER OPTIONS (CONTACT US FOR A QUOTE FOR THESE)	
	• Glass lockable door • Door left open alarm.	
	OPTIONAL TEMPERATURE DATA LOGGER	
	Full specifications for this data logger can be found in the User Manual found under the Resources tab.	
	Logger	
	Radio Power	1 mW (0 dBm)
	Transmission Range	Approximately 30.5 m (100 ft) line-of-sight
	Wireless Data Standard	Bluetooth Low Energy (Bluetooth Smart)
	Logger Operating Range	-30° to 70°C (-22° to 158°F), 0 to 95% RH (non-condensing)
	Logging Rate	1 second to 18 hours
	Time Accuracy	±1 minute per month at 25°C (77°F)
	Battery Type	Two AAA 1.5 V alkaline or lithium batteries, user-replaceable
	Battery Life	1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the InTemp app, excessive report generation, numerous audible alarms, and paging all impact battery life.
	Memory	128 KB (84,650 measurements, maximum)
	Full Memory Download Time	Approximately 60 seconds; may take longer the farther the device is from the logger
	LCD	LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range
	Dimensions	9.4 x 4.5 x 2.59 cm (3.7 x 1.77 x 1.02 inches)
	Weight	90.2 g (3.18 oz)
	Environmental Rating	IP54
	CE	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).
	External Temperature Probe	
	Range	-40° to 100°C (-40° to 212°F)
	Accuracy	±0.5°C from -15° to 80°C (±0.9°F from 5° to 176°F) ±1.0°C from -40° to -15°C (±1.8°F from -40° to 5°F) ±0.7°C from 80° to 100°C (±1.3°F from 176° to 212°F)
	Resolution	0.024°C at 25°C (0.04°F at 77°F)
	Drift	<0.1°C (0.18°F) per year
	Response Time	With 5 mL bottle: 10 minutes typical to 90% in air moving 1 m/s With 15 mL bottle: 20 minutes typical to 90% in air moving 1 m/s With 30 mL bottle: 25 minutes typical to 90% in air moving 1 m/s
	Cable Length	2 or 4 meter (6.56 or 13.12 feet) flat ribbon cable
	Ambient Temperature Sensor	
	Range	-30° to 70°C (-22° to 158°F)
	Accuracy	±0.5°C from -15° to 70°C (±0.9°F from 5° to 158°F) ±1.0°C from -30° to -15°C (±1.8°F from -22° to 5°F)
	Resolution	0.024°C at 25°C (0.04°F at 77°F)
	Drift	<0.1°C (0.18°F) per year
	Response Time	15 minutes typical to 90% in air moving 1 m/s
	Professional	
Ideal For	ACCUR8	
Brand	ACCUR8	
Typical applications	Life Sciences, Pharmaceutical, Vaccine Storage	
Measurements	Temperature	

Additional Options

Optional Temperature Logger with 2m Probe & 5ml Glycol Bottle	InTemp Temperature Data Logger (SKU: CX402-T205)
Optional Remote Cloud-based Access to Your Data	InTemp CX Internet Gateway (SKU: CX5000)
CX Gateway Service Plan Subscription - required with CX Internet Gateway	CX Gateway Service Plan Subscription (1 Year)