

Call our friendly team on +44 (0)1243 558270

Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 0UZ, UK www.tempcon.co.uk



HOBO MX2303 Wireless Temperature Data Logger with Two External Sensors - Optional Remote Monitoring

Product Images





Short Description

This data logger from Onset is designed to withstand harsh indoor/outdoor conditions.

Description

The HOBO MX2303 is a weatherproof data logger with two external temperature sensors. Leveraging Bluetooth Low Energy, the logger enables easy, fast set up and data download directly from your mobile device. For remote cloud-based access to your data and alerts, simply add the optional MX Gateway.

Key Features

- Convenient wireless setup and data download via Bluetooth Low Energy, or via the cloud with the optional MX Gateway
- View current data in real time with the free HOBOconnect app, and near real-time cloud-based monitoring with the optional MX Gateway
- Receive alert notifications for out-of-range conditions via email or SMS text message with the optional MX Gateway
- Visual alerts on the data logger and app
- Retrieve data in hard-to-reach locations
- Compact, weatherproof housing with built-in mounting system
- Share downloaded data easily from your mobile device
- Accuracy: +/- 0.2C°.

Additional Information

Doubtry of Manufacture Brand Onset HOBO Measurements Temperature Typical applications Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety MX2300 Features: - Convenient Wireless setup and download via Bluetooth Low Energy (100-foot range) - Retrieve data in hard-to-reach locations - Visual alarms alert you to out-of-range conditions - Compact, weather-proof housing with built-in mounting - View current data in real time with Onset's free HOBOmobile app - Share downloaded data easily from your mobile device - Accuracy: 4-0.2C* Dowload the HOBOconnect app: Contents - HOBO MX2303 2 Ext Temp Data Logger - Screws - Cable ties Ideal For Professional, Agronomy Power Battery only Temperature Sensor: Range - MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) - MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) - MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year - Accuracy - 4.0.2°C from 70 to 10°C (±0.45 from 32 to 158°F) - ±0.2°C from 70 to 10°C (±0.45 from 32 to 158°F) - ±0.2°C from 70 to 10°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only - Resolution - 0.04°C (0.018°F) per year		
Temperature Typical applications Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety MX2300 Features:	Country of Manufacture	United States
Typical applications Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety MX2300 Features:	Brand	Onset HOBO
Research, Food Safety Onset Product Series MX2300 Features:	Measurements	Temperature
Features: Convenient wireless setup and download via Bluetooth Low Energy (100-foot range) Retrieve data in hard-to-reach locations Visual alarms alert you to out-of-range conditions Compact, weatherproof housing with built-in mounting View current data in real time with Onset's free HOBOmobile app Share downloaded data easily from your mobile device Accuracy: +/- 0.2C° Dowload the HOBOconnect app: HOBO MX2303 2 Ext Temp Data Logger Screws Cable ties Ideal For Professional, Agronomy Power Battery only Temperature Sensor: Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.2°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from -40 to 10°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F) Drift	Typical applications	
Power Sensors • Convenient wireless setup and download via Bluetooth Low Energy (100-foot range) • Retrieve data in hard-to-reach locations • Nisual alarms alert you to out-of-range conditions • Compact, weatherproof housing with built-in mounting • View current data in real time with Onset's free HOBOmobile app • Share downloaded data easily from your mobile device • Accuracy: +/- 0.2C° Dowload the HOBOconnect app: I The Hobo MX2303 2 Ext Temp Data Logger • Screws • Cable ties Ideal For Professional, Agronomy Power Battery only Temperature Sensor: Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F)	Onset Product Series	MX2300
Contents • Screws • Cable ties Ideal For Professional, Agronomy Power Battery only Temperature Sensor: Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.25°C from 0 to 70°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F) Drift	Explanation	 Convenient wireless setup and download via Bluetooth Low Energy (100-foot range) Retrieve data in hard-to-reach locations Visual alarms alert you to out-of-range conditions Compact, weatherproof housing with built-in mounting View current data in real time with Onset's free HOBOmobile app Share downloaded data easily from your mobile device Accuracy: +/- 0.2C° Dowload the HOBOconnect app:
Power Battery only Temperature Sensor: Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F) Drift	Contents	• Screws
Temperature Sensor: Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F) Drift	Ideal For	Professional, Agronomy
Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F) Drift	Power	Battery only
	Sensors	Range MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year Accuracy ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only Resolution 0.04°C (0.072°F) Drift

Additional Options

Optional Remote Cloud Access to Your Data	MX Gateway for HOBO MX Data Loggers (SKU: MXGTW1)
	HOBOlink Service Plan (One Year Subscription (SKU: SP-620)) - one required per MX Gateway
Temperature Calibration Certificate	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)