

Tempcon Instrumentation Ford Lane Business Park Ford West Sussex BN18 0UZ, UK www.tempcon.co.uk



TFA Air CO2ntrol 5000 CO2 Monitor & Logger with Temperature and Humidity

Product Images



Short Description

The display shows the current CO2 content as well as a graphic history graph for the last 24 hours. It also displays the maximum and minimum values. The monitor also displays current temperature and humidity values on the screen.

Description

Monitor indoor air quality and carbon dioxide levels. Displays temperature, relative humidity and CO₂ simultaneously.

With an NDIR (non-dispersive infrared) CO₂ sensor, this unit is stable for long-term monitoring.

Key Features

- Data Logging to micro SD card (supplied)
- Data saves as CSV with time stamp history for downloading to any spreadsheet programs
- Logger function saves more than 1 million data records
- CO₂ measured value with LED traffic light display
- CO₂ Alarm function
- On screen historical values (minute, hour, day, week)
- Min/Max reading displayed on screen
- USB cable power supply
- Backlight.

Additional Information

CO2 Range 0 to 5000 ppm Display Resolution 1 ppm (0-1000); 5ppm (1000-2000); 10ppm (>2000) Noppm (>2000) Accuracy Over 3000 ppm ±7% of reading Warm up <30 seconds Temperature Range 0 to 50°C (32 to 122°F) Warm up 20 Minutes (63%) Resolution 0,1°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Paper Individual Paper 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 6 to 95% RH Resolution 1,0°C (0.1°F) Humidity Range 1,0°C (0.1	Brand	TFA Dostmann
healthier. Did you know higher levels of CO2 can often cause headaches, dizziness, concentration and long-term fatigue. If you suffer from these you may have excessively high concentration of carbon dioxide in your home or work place. For areas that have higher than average levels you may consider introducing plants that help to improve the balance between oxygen and carbon dioxide. Explanation Explanat		Display Resolution 1ppm (0-1000); 5ppm (1000-2000); 10ppm (>2000) Accuracy Over 3000 ppm ±7% of reading Warm up <30 seconds Temperature Range 0 to 50°C (32 to 122°F) Warm up 20 Minutes (63%) Resolution 0.1°C (0.1°F) Humidity Range 5 to 95% RH Resolution 1%
Measurements Air Quality, CO2, Humidity, Temperature Typical applications Environmental (Indoor), HVAC	Explanation	healthier. Did you know higher levels of CO2 can often cause headaches, dizziness, concentration and long-term fatigue. If you suffer from these you may have excessively high concentration of carbon dioxide in your home or work place. For areas that have higher than average levels you may consider introducing plants that help to improve the balance between oxygen and carbon dioxide. With this CO2 desktop unit you can monitor how polluted the air is in any area at home or work. A coloured traffic light display allows the CO2 values to be interpreted at a glance and changes from green to yellow to red depending on the air quality and the setting of the limit values. If a specified maximum value is exceeded, an acoustic signal can also warn of an excessively high CO2 concentration. This unit has a built in data logger function via SD card. In addition to the CO2 content, the device measures the temperature and humidity of the environment records the date and time. This extensive logger function enables over 1 million data records (CO2 / humidity / temperature with date and time) to be saved on the supplied micro SD card as a CSV file. The standard measuring interval of five seconds can be adjusted individually to: 5/30/60/300/600 seconds. The saved data can then be evaluated quickly and easily using any spreadsheet program. This station is supplied with power via a power pack included in the scope of delivery via a USB
Typical applications Environmental (Indoor), HVAC	Ideal For	Professional, Education, Amateur, Interested
	Measurements	Air Quality, CO2, Humidity, Temperature
Power USB Cable Power Supply	Typical applications	Environmental (Indoor), HVAC
	Power	USB Cable Power Supply