



HOBO Cellular Weather Station Kit - Advanced (includes Barometric Pressure & Solar Radiation Sensors)

Product Images



Short Description

The HOBO RX3000 Weather Station Advanced Kit provides instant access to site-specific air temperature, relative humidity, barometric pressure, solar radiation, rainfall and wind speed/direction data anywhere, anytime on your desktop or mobile device.

Buying in Volume, or Want Same Helpful Advice?

Call **+44 (0)1243 558270**, click on the webchat box below, or fill out our [contact form](#).

Description

Key Features

- Cloud-based 24/7 data access via [HOBOLink](#) web-enabled software platform
- 4G cellular communication (also works with 3G/2G)
- Solar powered
- Plug-and-play operation
- Alert notifications via text/email
- Rugged double-weatherproof enclosure.



Kit Components

- HOBO RX3000 Cellular Remote Monitoring Station Data Logger - [RX3004-00-01](#)
- 15W Solar Panel - [SOLAR-15W](#)
- Temperature/RH Smart Sensor with 2 metre cable - [S-THC-M002](#)
- Wind Speed and Direction Smart Sensor Set - [S-WSET-B](#)
- Barometric Pressure Smart Sensor - [S-BPB-CM50](#)
- Solar Radiation (Silicon Pyranometer) Smart Sensor - [S-LIB-M003](#)
- 0.2 mm Resolution Rain Gauge Smart Sensor with 2 metre cable - [S-RGB-M002](#)
- Full Cross-Arm for wind speed/direction sensors - [M-CAA](#)
- Solar Radiation Shield for temperature & RH sensor - [RS3-B](#)
- Solar Radiation Sensor Bracket - [M-LBB](#)

The RX3000 accepts up to 10 plug-and-play Smart Sensors, or up to 50 [HOBOnet](#) wireless sensors. Just plug in your sensor and it's automatically recognised – no programming, wiring, or calibration necessary.

Note: If your needs are different, you can create your own [customised RX3000 weather station](#) with the wide range of sensors available.

Additional Information

Brand	Onset HOBO
Country of Manufacture	United States
Explanation	RX3000 Range Specifications
	Operating Range -40° to 60°C (-40° to 140°F); no remote communications for battery voltage less than 3.9 V DC
	Smart Sensor Connectors 10
	Smart Sensor Network Cable Length 100 m (328 ft) maximum
	Smart Sensor Data Channels Maximum of 15 (some smart sensors use more than one data channel; see sensor manual for details)
	Module Slots 2
	Logging Rate 1 second (RX3001 and RX3002) or 1 minute (RX3003 and RX3004) to 18 hours
	Time Accuracy ±8 seconds per month in 0° to 40°C (32°F to 104°F) range; ±30 seconds per month in -40° to 60°C (-40° to 140°F) range
	Battery Type/Power Source 4 Volt, 10 Ahr, rechargeable sealed lead-acid; external power required using one of these options: AC power adapter (AC-U30), solar panel (SOLAR-xW), or external power source 5 V DC to 17 V DC with external DC power cable (CABLE-RX-PWR)
	Rechargeable Battery Service Life Typical 3-5 years when operated in the temperature range -20° to 40°C (-4°F to 104°F); operation outside this range will reduce the battery service life
	Memory 32 MB, 2 million measurements, continuous logging
	Alarm Notification Latency Logging interval plus 2-4 minutes, typical
	Enclosure Access Hinged door secured by two latches with eyelets for use with user-supplied padlocks
	LCD LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range
	Materials Outer enclosure: Polycarbonate/PBT blend with stainless steel hinge pins and brass inserts; Inner enclosure: Polycarbonate; Gaskets: Silicone rubber; Cable channel: EPDM rubber; Cable opening cover: Aluminum with ABS plastic thumb screws; U-Bolts: Steel with zinc dichromate finish
	Size 18.6 x 18.1 x 11.8 cm (7.3 x 7.1 x 4.7 in.); see diagrams on next page
	Weight 2.2 kg (4.85 lb)
	Mounting 3.8 cm (1.5 inch) mast or wall mount
	Environmental Rating Weatherproof enclosure, NEMA 4X (requires proper installation of cable channel system)
	 The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)
	 RX3002: FCC ID R68XPICOW, IC ID 3867A-XPICOW RX3003: FCC ID QIPPH56, IC ID 7830A-EH56; approved for use in Taiwan and Japan RX3004: FCC ID QIPPLS62-W, IC ID:7830A-PLS62W
	Wireless Radio RX3003: GSM/GPRS/EDGE: Quad band 850/900/1800/1900 MHz, UMTS/HSPA+: Five band 800/850/900/1900/2100 MHz RX3004: GSM/GPRS/EDGE: Quad band 850/900/1800/1900 MHz UMTS/HSPA+: Seven band 800/850/900/1800/1900/2100 MHz LTE: Twelve Band 700/800/850/900/1800/1900/2100/2600 MHz
	Antenna RX3003: Penta band RX3004: 4G LTE
	Ethernet (RX3001)
	Connector One RJ45/100BaseT
	Wi-Fi (RX3002)
	Network Standards IEEE 802.11b/g/n
	Frequency Range 2.412-2.484 GHz
	Antenna Connector 1, no diversity supported
	Data Rates 1, 2, 5.5, 11 Mbps (802.11b); 6, 9, 12, 18, 24, 36, 48, 54 Mbps (802.11g); 802.11n, HT20 MCS0 (6.5 Mbps) to HT20 MC87 (65 Mbps)
	Number of Selectable Radio Subchannels Up to 14 channels; profiles available will include USA, France, Japan, Spain, Canada, and "Other" (multiple countries)
	Radio Modulations OFDM, DSSS, DBPSK, DQPSK, CCK, 16QAM, 64QAM
	Security WEP 64/128, WPA-PSK, AES end-to-end encryption, WPA2, protocols not listed are not supported
	Maximum Receive Level -10 dBm (with PER <8%)
	Receiver Sensitivity -72 dBm for 54 Mbps, -87 dBm for 11 Mbps, -89 dBm for 5.5 Mbps, -90 dBm for 2.0 Mbps, -92 dBm for 1.0 Mbps
	Cellular (RX3003 and RX3004)
	Wireless Radio RX3003: GSM/GPRS/EDGE: Quad band 850/900/1800/1900 MHz, UMTS/HSPA+: Five band 800/850/900/1900/2100 MHz RX3004: GSM/GPRS/EDGE: Quad band 850/900/1800/1900 MHz UMTS/HSPA+: Seven band 800/850/900/1800/1900/2100 MHz LTE: Twelve Band 700/800/850/900/1800/1900/2100/2600 MHz
	Antenna RX3003: Penta band RX3004: 4G LTE
Ideal For	Professional
Onset Product Series	RX
Measurements	Barometric Pressure, Dew Point, Humidity, Rainfall, Solar Radiation, Temperature, Wind Direction, Wind Speed
Typical applications	Environmental (Outdoor), Field Research, Weather Monitoring
Power	Solar power with battery back-up


Station Model



HOBO RX3000 Remote Monitoring Data Logging Station

The HOBO RX3000 is Onset's next-generation remote data logging station that provides instant access to site-specific environmental data anywhere, anytime via the internet.

Solar Panel



HOBO SOLAR-15W - 15 Watt Solar Panel

This solar panel is ideal for very cloudy locations, higher latitudes, and/or when connecting analog sensors with high excitation power requirements.

Temperature & Humidity Smart Sensor



HOBO S-THC-M002 12-bit Temperature/Relative Humidity Smart Sensor (2m cable)

The HOBO 12-bit Temperature/Relative Humidity Smart Sensor is designed to work with all HOBO data loggers that accept Smart Sensors. All sensor parameters are stored inside the Smart Sensor, which automatically communicates configuration data information to the logger without any programming, calibration, or extensive user setup.

Wind Speed and Direction Smart Sensor Set



HOBO S-WSET-B Wind Smart Sensor Set

The Wind Sensor Set includes Onset's research-grade plug-and-play Wind Speed Smart Sensor and the Wind Direction Smart Sensor. This combination provides average wind speed, highest three-second wind gust and average wind direction for the measurement interval. These durable sensors will provide many years of accurate and reliable performance.

Rain Gauge Smart Sensor with 2 Metre Cable



S-RGB-M002 Rain Gauge Smart Sensor

The S-RGB-M002 Rain Gauge is scaled for metric measurements and is suitable for use with HOBO Weather Stations and compatible loggers.

The S-RGB-M002 measures up to 10 cm of rain per hour with a resolution of 0.2 mm and a maximum of 4000 tips per interval.

Barometric Pressure Smart Sensor



HOBO S-BPB-CM50 Barometric Pressure Smart Sensor

The Barometric Pressure Smart Sensor has a measurement range of 660 mb to 1070 mb (19.47 to 31.55 inHg), and can perform measurement averaging to obtain the highest accuracy. The operating temperature range for this sensor is -40° to 70°C (-40° to 158°F). This weatherproof smart sensor is mounted outside the logger enclosure.

Full Cross-Arm for Wind Speed and Direction Sensors



M-CAA -Weather Station Full Cross Arm

For use with Onset tripods or masts, the full cross arm assures unobstructed wind measurement. Full cross arm (91.2cm/36in) provides mounting for two wind sensors.

Solar Radiation Shield



HOBO RS3-B Solar Radiation Shield

The RS3-B Solar Radiation Shield protects external sensors from the effects of sunlight and rain to ensure high accuracy measurements and is designed to allow maximum air flow around the sensor.

Part No:
RS3-B

Solar Radiation Smart Sensor



HOBO S-LIB-M003 Solar Radiation (Silicon Pyranometer) Smart Sensor with 3m Cable

Measures light levels; rapid deployment, with no complicated programming or setup required; compatible with H21, H22, U30 and RX family loggers.

Solar Radiation Sensor Bracket



HOBO Light Sensor Bracket

The light sensor bracket is designed for use with tripods, masts, or flat surfaces.

Additional Options

Mounting Options	HOBO 2-Metre Tripod Kit (M-TPB-KIT)
	HOBO 3-Metre Tripod Kit (M-TPA-KIT)
Data Plan	Basic 4G Plan - 60 minutes interval - up to 22 sensors (SP-811)
	Standard 4G Plan - 10 minutes interval - up to 25 sensors (SP-813)
	Premium 4G Plan - 10 minutes interval - up to 65 sensors (SP-815)
Handheld Anemometer (to help you position weather station wind sensor in optimum location for maximum wind)	Kestrel 1000 (Pro-quality, made in USA)