




pHionics STs Series pH Water Quality Sensor

Product Images



Short Description

The pHionics STS Series pH sensor is meticulously engineered to meet your monitoring and control needs. **Low maintenance operation, rugged materials & seals, and ground loop elimination** all come standard. Just plug two wires into any pH monitoring/control system that accepts 4-20 mA inputs and **enjoy years of hassle-free operation.**

Description

The STs Series pH water quality sensor makes your job easier by providing years of trustworthy pH and temperature data via noise-resistant 4-20 mA signals.

The sensor has a large, double junction reference electrode for stable measurements over long periods of unmanned operation. In addition, our noise-reduction technology prevents ground loops and other forms of electrical interference for consistently accurate measurements.

A narrow diameter (0.75" or 1.9 cm) and fully sealed, submersible design allows the sensor to go anywhere you need to collect data while the durable, chemical-resistant housing and Kevlar-reinforced cable ensure many years (10+) of operation, even in polluted environments.

Key Features

- Large gel-filled, double-junction electrode providing stable 0-14 pH measurements for long periods of time
- Durable, chemical-resistant housing and cable
- Combination double-junction electrode with large reference reservoir
- Built-in 0-50°C temperature sensor (2nd channel)
- Chemical-resistant Delrin®, PVDF, and 316 Stainless Steel housing (Titanium optional)
- True 2-wire sensor for simple installation
- Solution ground
- Narrow diameter (0.75 inches or 1.9 cm)
- Removable electrode guard
- Fully submersible up to 70 psi
- Shielded, Kevlar®-reinforced, water-blocked polyurethane cable
- 4-20 mA signal capable of transmission up to 3 miles (with proper wire gauge)
- Automatic Temperature Compensation (2% per degree Celsius)
- Reversible Input Protection and Operation
- 2-second warm-up time
- Lowest power usage compared to other 4-20 mA pH sensors
- Isolated to prevent electrical interference and protect connected devices
- Signal conditioning to remove background noise.

Applications

- Groundwater Monitoring
- Agricultural Run-off
- Mining Pollution
- Industrial Effluent Monitoring
- Wastewater Treatment
- Environmental Remediation
- Aquaculture.

Built-To-Last

With proper care, these sensors are designed for many years of reliable pH monitoring in harsh conditions. The truly unique aspect of the STs Series is that every part, including the cable, is easily replaceable in the event of wear/damage. This considerably extends their lifespan to save your company money. It also keeps

waste out of landfills to support sustainable business practices.

Ground Loop Elimination

If you ever have a pH sensor sending erratic measurements and can't figure out why, then there may be a "ground loop". A ground loop occurs when the electrical circuit has multiple paths to ground that cause interference. This issue can be very difficult to detect and fix. The best way to avoid ground loops is with input/output electrical isolation, which is built into every pHionics sensor.

Low Maintenance

Very little is required to keep these sensors up. Just perform periodic calibrations and replace the electrode every few years. Electrode replacement is a 60-second procedure that is easily performed in the field without any tools.

Additional Information

Brand	pHionics																																																												
Country of Manufacture	United States																																																												
Explanation	<div><div><div>Specifications</div><div>pH Sensor</div><table><tr><td>Output</td><td>4-20 mA</td></tr><tr><td>pH Range</td><td>0-14 pH</td></tr><tr><td>Operational Temperature Range</td><td>0-70°C</td></tr><tr><td>Electrode Type</td><td>Silver/silver chloride, double junction, replaceable gel electrode</td></tr><tr><td>Transmitter Type</td><td>2-wire</td></tr><tr><td>Pressure Range</td><td>0-70 psi</td></tr><tr><td>Automatic Temperature Compensation</td><td>0-70°C</td></tr><tr><td>Isolation</td><td>600 VDC</td></tr><tr><td>Power Supply Voltage</td><td>8-40 VDC</td></tr><tr><td>Warm-up Time</td><td>2 seconds</td></tr><tr><td>Response time</td><td>95% < 5 seconds</td></tr><tr><td>Wetted Materials</td><td>316 Stainless Steel, Delrin®, Viton™, glass, epoxy</td></tr><tr><td>Length</td><td>14.25 in (36.20 cm)</td></tr><tr><td>Width</td><td>0.750 in (1.9 cm) maximum</td></tr><tr><td>Weight (No cable)</td><td>0.50 lbs (0.227 kg)</td></tr><tr><td>Linearity</td><td>±0.014 pH*</td></tr><tr><td>Accuracy</td><td>±0.014 pH*</td></tr><tr><td>Sensitivity</td><td>±0.01 pH</td></tr><tr><td>Stability</td><td>±0.03 pH per year</td></tr><tr><td>Repeatability</td><td>±0.01 pH</td></tr></table></div><div><div>*After proper calibration</div><div>Temperature Sensor</div><table><tr><td>Output</td><td>4-20 mA</td></tr><tr><td>Temperature Range</td><td>0-50°C</td></tr><tr><td>Accuracy</td><td>+/- 1°C</td></tr><tr><td>Linearity</td><td>+/- 0.5°C</td></tr><tr><td>Power Supply Voltage</td><td>7-40 VDC</td></tr></table></div><div><div>Cable</div><table><tr><td>Cable Material</td><td>Polyurethane</td></tr><tr><td>Type</td><td>4 conductor, Kevlar® reinforced, water blocked, shielded, twisted-pair wiring</td></tr><tr><td>Maximum Distance</td><td>3 miles</td></tr><tr><td>Resistance per 1000 ft (304.8 m)</td><td>26 Ohms</td></tr><tr><td>Replaceable?</td><td>Yes</td></tr></table></div><div><div>pHionics products comply fully with all applicable EU Directives to bear the CE Mark. Delrin® and Kevlar® are registered trademarks of DuPont™. Viton™ is a trademark of Chemours.</div></div></div>	Output	4-20 mA	pH Range	0-14 pH	Operational Temperature Range	0-70°C	Electrode Type	Silver/silver chloride, double junction, replaceable gel electrode	Transmitter Type	2-wire	Pressure Range	0-70 psi	Automatic Temperature Compensation	0-70°C	Isolation	600 VDC	Power Supply Voltage	8-40 VDC	Warm-up Time	2 seconds	Response time	95% < 5 seconds	Wetted Materials	316 Stainless Steel, Delrin®, Viton™, glass, epoxy	Length	14.25 in (36.20 cm)	Width	0.750 in (1.9 cm) maximum	Weight (No cable)	0.50 lbs (0.227 kg)	Linearity	±0.014 pH*	Accuracy	±0.014 pH*	Sensitivity	±0.01 pH	Stability	±0.03 pH per year	Repeatability	±0.01 pH	Output	4-20 mA	Temperature Range	0-50°C	Accuracy	+/- 1°C	Linearity	+/- 0.5°C	Power Supply Voltage	7-40 VDC	Cable Material	Polyurethane	Type	4 conductor, Kevlar® reinforced, water blocked, shielded, twisted-pair wiring	Maximum Distance	3 miles	Resistance per 1000 ft (304.8 m)	26 Ohms	Replaceable?	Yes
Output	4-20 mA																																																												
pH Range	0-14 pH																																																												
Operational Temperature Range	0-70°C																																																												
Electrode Type	Silver/silver chloride, double junction, replaceable gel electrode																																																												
Transmitter Type	2-wire																																																												
Pressure Range	0-70 psi																																																												
Automatic Temperature Compensation	0-70°C																																																												
Isolation	600 VDC																																																												
Power Supply Voltage	8-40 VDC																																																												
Warm-up Time	2 seconds																																																												
Response time	95% < 5 seconds																																																												
Wetted Materials	316 Stainless Steel, Delrin®, Viton™, glass, epoxy																																																												
Length	14.25 in (36.20 cm)																																																												
Width	0.750 in (1.9 cm) maximum																																																												
Weight (No cable)	0.50 lbs (0.227 kg)																																																												
Linearity	±0.014 pH*																																																												
Accuracy	±0.014 pH*																																																												
Sensitivity	±0.01 pH																																																												
Stability	±0.03 pH per year																																																												
Repeatability	±0.01 pH																																																												
Output	4-20 mA																																																												
Temperature Range	0-50°C																																																												
Accuracy	+/- 1°C																																																												
Linearity	+/- 0.5°C																																																												
Power Supply Voltage	7-40 VDC																																																												
Cable Material	Polyurethane																																																												
Type	4 conductor, Kevlar® reinforced, water blocked, shielded, twisted-pair wiring																																																												
Maximum Distance	3 miles																																																												
Resistance per 1000 ft (304.8 m)	26 Ohms																																																												
Replaceable?	Yes																																																												
Ideal For	Professional																																																												